



US00D343346S

# United States Patent [19]

Sadler

[11] Patent Number: **Des. 343,346**

[45] Date of Patent: **\*\* Jan. 18, 1994**

[54] **CLEAT REMOVAL AND INSTALLATION TOOL**

[76] Inventor: **Charles Sadler, 119 Williamsburg, Bullard, Tex. 75757**

[\*\*] Term: **14 Years**

[21] Appl. No.: **801,843**

[22] Filed: **Dec. 3, 1991**

[52] U.S. Cl. .... **D8/70**

[58] Field of Search ..... **D8/70; 81/176.15, 176.1, 81/176.2, 124.2, 121.1, 125; D21/234**

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

2,881,648	4/1959	Hottle .....	81/176.15
4,823,650	4/1989	Tuttle .....	81/176.15
5,048,378	9/1991	Nikolas .....	81/176.15
5,072,634	12/1991	Ryder .....	81/176.15

*Primary Examiner*—Nelson C. Holtje

*Assistant Examiner*—J. H. Musgrove  
*Attorney, Agent, or Firm*—Ronald B. Sefrna

[57] **CLAIM**

The ornamental design for a cleat removal and installation tool, as shown and described.

**DESCRIPTION**

FIG. 1 is a front elevational view of a cleat removal tool showing my new design;


FIG. 2 is a typical side elevational view;

FIG. 3 is a top plan view;

FIG. 4 is a bottom plan view; and,

FIG. 5 is a sectional view, taken along line 5—5 of FIG. 3.

The cleat removal and installation tool of the invention includes a concave depression extending into the interior of the tool from the bottom end, and an aperture extending farther into the interior of the tool from the center of the concave depression in coaxial alignment with the longitudinal axis of the tool, as illustrated in the sectioned view of FIG. 5.






FIGURE 1




FIGURE 2




FIGURE 5




FIGURE 3




FIGURE 4