



US00D344038S

# United States Patent [19]

[11] Patent Number: **Des. 344,038**

Phillips et al.

[45] Date of Patent: **\*\* Feb. 8, 1994**

[54] SAFETY STRAP FOR USE WITH WATCHES, COMPASSES AND DEPTH GAUGES

3,307,872	3/1967	Murcott	24/306
3,747,171	7/1973	Montague	24/306
3,947,927	4/1976	Rosenthal	24/16 R
4,878,274	11/1989	Patricy	24/306

[76] Inventors: **Mitchell J. Phillips; Rayne Simpson**, both of 124 Mitchell Street, Glebe, New South Wales 2038, Australia

*Primary Examiner*—A. Hugo Word  
*Assistant Examiner*—R. Seifert  
*Attorney, Agent, or Firm*—Ladas & Parry

[\*\*] Term: **14 Years**

[57] **CLAIM**

[21] Appl. No.: **784,040**

The ornamental design for a safety strap for use with watches, compasses and depth gauges, as shown and described.

[22] Filed: **Oct. 28, 1991**

[52] U.S. Cl. .... **D11/5; D11/3**

[58] Field of Search ..... 63/1.1, 2; 74/526; D3 DIG. 61, DIG. 62; 224/257; 24/306, 16 R, 371; 248/548; D11/1-5


**DESCRIPTION**

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

D. 249,939	10/1978	Dammons	D11/2
D. 258,812	4/1981	Cox	D11/2
D. 267,555	1/1983	Cox	D11/2
D. 271,160	11/1983	Sherwin	D11/2
D. 317,730	6/1991	Mo	D11/5
D. 335,217	5/1993	Seitz	D11/5
D. 335,263	5/1993	Willis	D11/5

FIG. 1 is a perspective view of a safety strap for use with watches, compasses and depth gauges in a buckled condition showing my new design;  
FIG. 2 is a top plan view thereof;  
FIG. 3 is a side elevational view, the other side being a mirror image thereof;  
FIG. 4 is a front elevational view thereof;  
FIG. 5 is a rear elevational view thereof;  
FIG. 6 is a bottom plan view thereof; and  
FIG. 7 is a perspective view thereof in an unbuckled condition.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

