



US00D344261S

United States Patent [19]

[11] Patent Number: **Des. 344,261**

Watanabe

[45] Date of Patent: **** Feb. 15, 1994**

[54] **BATTERY CHARGER FOR A CELLULAR PHONE BATTERY**

[75] Inventor: **Hirotoishi Watanabe**, Tokyo, Japan

[73] Assignee: **Funai Electric Engineering Co., Ltd.**, Tokyo, Japan

[**] Term: **14 Years**

[21] Appl. No.: **900,341**

[22] Filed: **Jun. 17, 1992**

[30] **Foreign Application Priority Data**

Dec. 20, 1991 [JP] Japan 3-38262

[52] U.S. Cl. **D13/107**

[58] Field of Search 320/2, 3, 4, 15; D13/107, 108, 144; D14/114, 217, 218, 240

[56] **References Cited**

U.S. PATENT DOCUMENTS

5,162,719 1/1992 Tomura et al. 320/15 X

OTHER PUBLICATIONS

Published Japanese application No. 61-46504, Oct. 27, 1987. Located in D13/107 non-patent literature. Eveready RF2 Battery Charger on Manual cover ©1989. Located in D13/107 non-patent literature.


Primary Examiner—Wallace R. Burke
Assistant Examiner—Joel Sincavage
Attorney, Agent, or Firm—Lackebach Siegel Marzullo Aronson & Greenspan

[57] **CLAIM**

The ornamental design for a battery charger for a cellular phone battery, as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of a battery charger for a cellular phone battery showing my new design; FIG. 2 is a rear elevational view of a battery charger for a cellular phone battery with the plug prongs in the retracted position; FIG. 3 is a front elevational view thereof; FIG. 4 is a right side elevational view thereof; FIG. 5 is a bottom plan view thereof; and, FIG. 6 is a perspective view thereof.






FIG. 1




FIG. 2




FIG. 3



FIG. 4




FIG. 5




FIG. 6