



US00D344261S

United States Patent [19]

Watanabe

[11] Patent Number: Des. 344,261

[45] Date of Patent: ** Feb. 15, 1994

[54] BATTERY CHARGER FOR A CELLULAR PHONE BATTERY

[75] Inventor: Hirotooshi Watanabe, Tokyo, Japan

[73] Assignee: Funai Electric Engineering Co., Ltd., Tokyo, Japan

[**] Term: 14 Years

[21] Appl. No.: 900,341

[22] Filed: Jun. 17, 1992

[30] Foreign Application Priority Data

Dec. 20, 1991 [JP] Japan 3-38262

[52] U.S. Cl. D13/107

[58] Field of Search 320/2, 3, 4, 15;
D13/107, 108, 144; D14/114, 217, 218, 240

[56] References Cited

U.S. PATENT DOCUMENTS

5,162,719 1/1992 Tomura et al. 320/15 X

OTHER PUBLICATIONS

Published Japanese application No. 61-46504, Oct. 27, 1987. Located in D13/107 non-patent literature.
Eveready RF2 Battery Charger on Manual cover ©1989. Located in D13/107 non-patent literature.

Primary Examiner—Wallace R. Burke

Assistant Examiner—Joel Sincavage

Attorney, Agent, or Firm—Lackebach Siegel Marzullo Aronson & Greenspan

[57] CLAIM

The ornamental design for a battery charger for a cellular phone battery, as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of a battery charger for a cellular phone battery showing my new design;


FIG. 2 is a rear elevational view of a battery charger for a cellular phone battery with the plug prongs in the retracted position;

FIG. 3 is a front elevational view thereof;

FIG. 4 is a right side elevational view thereof;

FIG. 5 is a bottom plan view thereof; and,

FIG. 6 is a perspective view thereof.






FIG. 1




FIG. 2




FIG. 3



FIG. 4




FIG. 5




FIG. 6