



US00D346954S

United States Patent [19] Vandermast

[11] Patent Number: **Des. 346,954**

[45] Date of Patent: **** May 17, 1994**

[54] **LOCKING FASTENER**

[75] Inventor: **Nueboch Vandermast, Flippin, Ark.**

[73] Assignee: **Ark Plas Products, Inc., Flippin, Ark.**

[**] Term: **14 Years**

[21] Appl. No.: **563**

[22] Filed: **Oct. 19, 1992**

[52] U.S. Cl. **D8/382**

[58] Field of Search **D8/382, 394; 24/67.1, 24/16 PB, 67 R, 103; 411/337, 372; 402/8, 21, 62, 68, 61, 63; D19/32**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 214,153	5/1969	Merser	D20/99
1,171,098	2/1916	Dalton	.	
1,237,034	8/1917	Harris	.	
1,374,713	4/1921	Bell	.	
1,841,989	1/1932	Smith	.	
2,132,950	10/1938	Green	.	
2,381,204	8/1945	Cardoza	129/12
2,440,038	8/1948	Baker	.	
2,780,128	2/1957	Rapata	.	
2,891,554	6/1959	Foster	129/23
3,086,265	4/1963	Orenick et al.	24/30.5
3,251,260	5/1966	Serdechny	.	
3,265,426	8/1966	Brooks et al.	292/307
3,290,080	12/1966	Dawson	292/322
3,422,499	1/1969	Merser	24/16
3,462,802	8/1969	Merser	24/16
3,588,963	6/1971	Moberg	24/16
3,712,655	1/1973	Fuehrer	292/321
4,093,288	6/1978	Suzuki	292/321
4,232,427	11/1980	Mawhinney et al.	24/103
4,930,927	6/1990	Dumas	402/63

FOREIGN PATENT DOCUMENTS

3204087	8/1963	Fed. Rep. of Germany	402/63
153800	6/1990	Japan	402/63

OTHER PUBLICATIONS

Richo Plastic Co, Parts Cat. p. 16.

Primary Examiner—B. J. Bullock
Attorney, Agent, or Firm—Stephen D. Carver

[57] **CLAIM**

The ornamental design for a locking fastener, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a locking fastener showing my new design;

FIG. 2 is a side elevational view of the male element shown separately for clarity of illustration, all sides being identical;

FIG. 3 is a top plan view of FIG. 2;

FIG. 4 is a bottom plan view of FIG. 2;

FIG. 5 is a perspective view of the female element, also shown separately for clarity of illustration;

FIG. 6 is a bottom plan view of FIG. 5, the top being identical;

FIG. 7 is a side elevational view of FIG. 5, all sides being identical;

FIG. 8 is a sectional view taken in the direction of the arrows on line 8—8 of FIG. 6;

FIG. 9 is a sectional view taken in the direction of the arrows on line 9—9 of FIG. 6;

FIG. 10 is a perspective view of a second embodiment of the design of FIG. 1, the only difference being the configuration of the female element;

FIG. 11 is a perspective view of the female element of FIG. 10, shown separately for clarity of illustration;

FIG. 12 is a bottom plan view of FIG. 11;

FIG. 13 is a top plan view of FIG. 11;

FIG. 14 is a side elevational view of FIG. 11, all sides being identical;

FIG. 15 is a sectional view taken in the direction of the arrows on line 15—15 of FIG. 12; and,

FIG. 16 is a sectional view taken in the direction of the arrows on line 16—16 of FIG. 12.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7



FIG. 8



FIG. 9



FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15



FIG. 16

