



US00D348376S

United States Patent [19]

[11] Patent Number: **Des. 348,376**

Röhrig

[45] Date of Patent: **** Jul. 5, 1994**

[54] **CLOSEABLE DRINKING CUP**

[75] Inventor: **Peter Röhrig, Vienna, Austria**

[73] Assignee: **Mam Babyartikel Gesellschaft m.b.H., Vienna, Austria**

[**] Term: **14 Years**

[21] Appl. No.: **948,815**

[22] Filed: **Sep. 17, 1992**

[30] **Foreign Application Priority Data**

Mar. 20, 1992 [AT] Austria MU-1010/92

[52] U.S. Cl. **D7/510; D7/511; D7/534**

[58] Field of Search **D7/387, 392.1, 372, D7/396.2, 396.3, 397, 398, 602, 507, 509, 510, 511, 524, 532, 533, 535, 536, 537, 619, 534, 543, 605; D9/560, 542, 338, 564, 551, 533, 443, 539; 215/11.1; 220/712, 717, 713; D12/114; D24/197, 199**

[56] **References Cited**

U.S. PATENT DOCUMENTS

- D. 208,950 10/1967 Hobbs et al. D9/533
- D. 233,972 12/1974 Juhlin 220/713 X
- D. 281,861 12/1985 Jones et al. D9/542 X
- D. 302,727 8/1989 Ryan et al. D24/197
- D. 303,150 8/1989 Falcon D24/199
- D. 316,652 5/1991 Hunter D7/511 X
- D. 333,704 3/1993 Malcolm D24/197
- 4,925,052 5/1990 Betka 220/719

- 4,961,510 10/1990 Dvoracek 220/717 X
- 5,165,579 11/1992 Lund 220/717 X
- 5,207,338 5/1993 Sandhu D7/534 X



Primary Examiner—Alan P. Douglas
Assistant Examiner—M. N. Pandozzi
Attorney, Agent, or Firm—Abelman Frayne & Schwab

[57] **CLAIM**

The ornamental design for a closeable drinking cup, as shown and described.

DESCRIPTION

FIG. 1 is a plan view of the closeable drinking cup when in an open condition;
 FIG. 2 is an underside plan view of FIG. 1;
 FIG. 3 is a right-hand side elevation of the closeable drinking cup, the opposite side thereof being a mirror image of FIG. 3;
 FIG. 4 is a front elevation thereof;
 FIG. 5 is a rear elevation;
 FIG. 6 is an underside plan view of the lid portion of FIGS. 1-11;
 FIG. 7 is a plan view of the closeable drinking cup when in a closed condition;
 FIG. 8 is an underside plan view of FIG. 7;
 FIG. 9 is a front elevation of the closeable drinking cup when in a closed position;
 FIG. 10 is a rear elevation thereof corresponding with FIG. 9; and,
 FIG. 11 is a right-side elevation thereof; the left hand side being a mirror image of FIG. 11.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11