



US00D348533S

United States Patent [19]

[11] Patent Number: **Des. 348,533**

Herst et al.

[45] Date of Patent: **** Jul. 5, 1994**

[54] **INDIRECT LIGHTING FIXTURE**

[75] Inventors: **Douglas J. Herst, Ross; Utkan Salman**, Emeryville, both of Calif.

[73] Assignee: **Peerless Lighting Corporation**, Berkeley, Calif.

[**] Term: **14 Years**

[21] Appl. No.: **11,393**

[22] Filed: **Aug. 3, 1993**

Related U.S. Application Data

[60] Continuation-in-part of Ser. No. 260,358, Oct. 20, 1988, Pat. No. Des. 311,967, and a continuation-in-part of Ser. No. 502,663, Apr. 2, 1990, abandoned, and a continuation-in-part of Ser. No. 555,146, Jul. 19, 1990, abandoned, which is a division of Ser. No. 588,971, Sep. 27, 1990, Pat. No. Des. 341,439.

[52] U.S. Cl. **D26/85; D26/76**

[58] Field of Search 362/216, 217, 220, 222, 362/223, 224, 147, 362; D26/72, 74-92

[56] **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|------------|---------|----------------------|-----------|
| D. 110,165 | 6/1938 | Arenburg | D26/76 X |
| D. 131,195 | 1/1942 | Hass | D26/76 |
| D. 136,797 | 12/1943 | Mareck | D26/76 |
| D. 139,669 | 12/1944 | Lippincott | D26/76 |
| D. 140,107 | 1/1945 | Lippincott | D26/76 |
| D. 185,410 | 6/1959 | Bodian et al. | D26/76 |
| D. 192,607 | 4/1962 | Cooke | D26/76 |
| D. 208,572 | 9/1967 | Wakefield | D26/76 |
| D. 311,967 | 11/1990 | Herst et al. | D26/76 X |
| 2,631,225 | 3/1953 | Gadomski | D26/78 X |
| 2,770,717 | 11/1956 | Schwartz et al. | 362/222 |
| 4,493,013 | 1/1985 | Hawkins | 362/362 X |
| 4,667,275 | 5/1987 | Herst et al. | 362/223 |

OTHER PUBLICATIONS

Architectural Forum, May-1958, p. 180, Fluorescent Lighting Fixture.

Thomas Industries, Inc. Low Profile Fluorescent Fixture brochure, 1984, p. 1, Ceiling Fixture.

Primary Examiner—Susan J. Lucas
Attorney, Agent, or Firm—Donald L. Beeson

[57] **CLAIM**

The ornamental design for an indirect lighting fixture, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of an indirect lighting fixture showing our new design;

FIG. 2 is a right side elevational view thereof on an enlarged scale, the left side being a mirror image thereof;

FIG. 3 is a front elevational view thereof, the rear elevational view being a mirror image thereof;

FIG. 4 is a bottom plan view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a front perspective view of a second embodiment of our new design;

FIG. 7 is a right side elevational view thereof on an enlarged scale, the left side being a mirror image thereof;

FIG. 8 is a front elevational view thereof, the rear elevational view being a mirror image thereof;

FIG. 9 is a bottom plan view thereof;

FIG. 10 is a top plan view thereof;

FIG. 11 is a front perspective view of a third embodiment of our new design;




FIG. 12 is a right side elevational view thereof on an enlarged scale, the left side being a mirror image thereof;

FIG. 13 is a front elevational view thereof, the rear elevational view being a mirror image thereof;

FIG. 14 is a bottom plan view thereof; and,

FIG. 15 is a top plan view thereof.

The broken line showing of lamps in the top plan views of the illustrated embodiments of the invention is for illustrative purposes only and forms no part of the claimed design.






FIG._1




FIG._5




FIG. 2




FIG. 3




FIG. 4




FIG._6




FIG._10




FIG._7




FIG._8




FIG._9




FIG. 11




FIG. 15




FIG. 12




FIG. 13




FIG. 14