



US00D348599S

United States Patent [19]

[11] Patent Number: **Des. 348,599**

Sakai

[45] Date of Patent: **** Jul. 12, 1994**

[54] **KNIFE**

[75] Inventor: **Kimiyuki Sakai, Seki, Japan**

[73] Assignee: **Gerber Sakai, Seki, Japan**

[**] Term: **14 Years**

[21] Appl. No.: **1,388**

[22] Filed: **Nov. 12, 1992**

[52] U.S. Cl. **D8/99; D22/118**

[58] Field of Search **D8/98, 99; 30/156, 157, 30/160, 161, 151, 152, 154, 155; D22/118**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 230,562	3/1974	Fellows	D8/99
D. 230,696	3/1974	Evrell	D8/99
D. 256,983	9/1980	Fogle	D8/99
D. 259,697	6/1981	Brizzolara, Jr.	D8/107
D. 302,934	8/1989	Finn	D8/99
D. 304,154	10/1989	Osterhout	D8/99
D. 306,817	3/1990	McMorrough	D8/99

OTHER PUBLICATIONS

Blade Magazine, Jul./Aug. 1988, p. 5 Lockback Knives at bottom right.

Primary Examiner—Bernard Ansher

Assistant Examiner—Philip Hyder

Attorney, Agent, or Firm—Hickman & Beyer

[57] **CLAIM**

The ornamental design for a knife, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a knife showing my new design;

FIG. 2 is a rear elevational view thereof;

FIG. 3 is a top plan view thereof;

FIG. 4 is a bottom plan view thereof;

FIG. 5 is a left side view thereof;

FIG. 6 is a right side view thereof;

FIG. 7 is a perspective view thereof;

FIG. 8 is a front elevational view thereof in an opened position;

FIG. 9 is a rear elevational view thereof in the opened position;

FIG. 10 is a top plan view thereof in the opened position;

FIG. 11 is a bottom plan view thereof in the opened position;

FIG. 12 is a left side view thereof in the opened position;

FIG. 13 is a right side view thereof in the opened position;

FIG. 14 is a perspective view thereof in the opened position;

FIG. 15 is a front elevational view of modified embodiment thereof;

FIG. 16 is a top plan view of the modified embodiment in a first opened position;

FIG. 17 is a bottom plan view of the modified embodiment in the first opened position;

FIG. 18 is a left side view of the modified embodiment in the first opened position;

FIG. 19 is a right side view of the modified embodiment in the first opened position;

FIG. 20 is a perspective view of the modified embodiment in the first opened position;

FIG. 21 is a front elevational view of the modified embodiment in a second opened position;


FIG. 22 is a top plan view of the modified embodiment in the second opened position;

FIG. 23 is a bottom plan view of the modified embodiment in the second opened position;

FIG. 24 is a left side view of the modified embodiment in the second opened position;

FIG. 25 is a right side view of the modified embodiment in the second opened position; and,

FIG. 26 is a perspective view of the modified embodiment in the second opened position.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24



FIG. 25




FIG. 26