



US00D348900S

United States Patent [19] Vogel

[11] Patent Number: **Des. 348,900**
[45] Date of Patent: **** Jul. 19, 1994**

[54] **CORNER CONDUIT FOR A PNEUMATICALLY-PROPELLED CARRIER SYSTEM**

[75] Inventor: **Victor J. Vogel, Oak Ridge, N.J.**

[73] Assignee: **Mosler Inc., Hamilton, Ohio**

[**] Term: **14 Years**

[21] Appl. No.: **948,769**

[22] Filed: **Sep. 14, 1992**

[52] U.S. Cl. **D18/35; 406/191; D23/393**

[58] Field of Search **406/191, 110-111; 138/DIG. 4, DIG. 11; D18/35; D23/387, 393**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 259,571	6/1981	Arasim, Jr. et al.	D18/35
530,747	12/1894	Carville	406/111
1,921,056	8/1933	Walker	285/179
2,216,864	10/1940	Wasmund	285/156
3,305,192	2/1967	Todt et al.	406/111
3,930,377	1/1976	Utter	406/191
3,964,512	6/1976	Dumas	406/191
4,059,246	11/1977	Anders et al.	406/110
4,455,112	6/1984	Anders	406/110
4,792,263	12/1988	Podoll	406/111
4,976,288	12/1990	Steele et al.	406/191

FOREIGN PATENT DOCUMENTS

629891	4/1936	Fed. Rep. of Germany	406/193
34304	1/1956	Fed. Rep. of Germany	406/193
1289792	2/1969	Fed. Rep. of Germany	406/191
2228695	12/1974	France	406/110
0071075	6/1977	Japan	406/191
0207324	11/1984	Japan	406/191
310090	9/1971	U.S.S.R.	138/DIG. 11
498236	3/1976	U.S.S.R.	406/191

537910	1/1977	U.S.S.R.	406/191
0796120	1/1981	U.S.S.R.	406/191
0927684	5/1982	U.S.S.R.	406/191
1044565	9/1983	U.S.S.R.	406/191
1414732	8/1988	U.S.S.R.	406/191
1627476	2/1991	U.S.S.R.	406/191

OTHER PUBLICATIONS

Dwg. D-F71799, "Expanded Bend Trans Vista-3 Teller Unit," Mosler/Airmatic Systems Div. (1981).

Dwg. C-F51098, "Guide Outer Expanded Bend Trans Vista Teller Unit," Mosler/Airmatic Systems Div. (1972).

Dwg. C-F71800, "Expanded Bend TRV-3 Teller Unit," Mosler/Airmatic Systems Div. (1981).

Dwg. B-F51092, "Guide Inner Expanded Bend Trans Vista Teller Unit," Mosler/Airmatic Systems Div. (1973).

Primary Examiner—Cathy Anne MacCormac
Attorney, Agent, or Firm—Wood, Herron & Evans

[57] **CLAIM**

The ornamental design for a corner conduit for a pneumatically propelled carrier system, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a 45° embodiment, depicting the top and front of the corner assembly design of this invention;

FIG. 2 is a perspective view, depicting the bottom and rear of the embodiment of FIG. 1;


FIG. 3 is a front elevational view thereof, with the rear elevational view thereof being a mirror image;

FIG. 4 is a left side elevational view thereof;

FIG. 5 is a right side elevational view thereof;

FIG. 6 is a top plan view thereof; and,

FIG. 7 is a bottom plan view thereof.






FIG. 1




FIG. 2




FIG. 4




FIG. 3




FIG. 5




FIG. 6




FIG. 7