



US00D350255S

# United States Patent [19]

Daenen et al.

[11] Patent Number: Des. 350,255

[45] Date of Patent: \*\* Sep. 6, 1994

[54] PITCHER WITH ROCKING SEAL

[75] Inventors: Robert H. C. M. Daenen, Essene, Belgium; Stig Lillelund, Gentofte, Denmark

[73] Assignee: Dart Industries Inc., Deerfield, Ill.

[\*\*] Term: 14 Years

[21] Appl. No.: 2,924

[22] Filed: Dec. 23, 1992

[52] U.S. Cl. .... D7/317; D7/316; D7/318

[58] Field of Search ..... D7/317, 322, 321, 319, D7/318, 316, 312, 598, 600, 538, 507, 500, 300, 509, 510, 511, 539, 540, 542, 543; 222/465.1, 469, 470, 471, 475

[56] References Cited

## U.S. PATENT DOCUMENTS

|            |         |               |       |          |
|------------|---------|---------------|-------|----------|
| D. 215,471 | 9/1969  | Gulotia       | ..... | D7/317   |
| D. 218,473 | 8/1970  | Asch          | ..... | D7/318   |
| D. 229,657 | 12/1973 | Cyren         | ..... | D7/317   |
| D. 251,765 | 5/1979  | Okazaki       | ..... | D7/321   |
| D. 254,240 | 2/1980  | Morin         | ..... | D7/321   |
| D. 270,602 | 9/1983  | Fritz         | ..... | D7/319   |
| D. 272,225 | 1/1984  | Decoster      | ..... | D7/316 X |
| D. 283,584 | 4/1986  | Morin         | ..... | D7/317   |
| D. 301,296 | 5/1989  | Hsu           | ..... | D7/317   |
| D. 303,904 | 10/1989 | Wolfden       | ..... | D7/317   |
| D. 306,547 | 3/1990  | Wolfden       | ..... | D7/317   |
| D. 312,551 | 12/1990 | De Coster     | ..... | D7/319   |
| D. 312,552 | 12/1990 | Carlson       | ..... | D7/321   |
| D. 312,745 | 12/1990 | Daenen et al. | ..... | D7/319 X |
| D. 330,305 | 10/1992 | Giugiaro      | ..... | D7/317 X |
| D. 339,023 | 9/1993  | De Coster     | ..... | D7/318   |
| 4,655,373  | 4/1987  | Essen         | ..... | D7/318 X |

## OTHER PUBLICATIONS

Pitcher #10, Design 404 Aug. 1982, p. 31.

Primary Examiner—Alan P. Douglas

Assistant Examiner—Marianne N. Pandozzi

Attorney, Agent, or Firm—John A. Doninger

[57] CLAIM

The ornamental design for a pitcher with rocking seal, as shown and described.

## DESCRIPTION

FIG. 1 is a top and side perspective view of a pitcher with rocking seal showing our new design;

FIG. 2 is a top plan view thereof;

FIG. 3 is a bottom plan view thereof;

FIG. 4 is a side elevation view thereof, the opposite side elevation being a mirror image;

FIG. 5 is a front elevation view thereof;

FIG. 6 is a rear elevation view thereof;

FIG. 7 is an exploded side elevation view thereof;

FIG. 8 is a cross-section view thereof on line 8—8 in FIG. 2;

FIG. 9 is on a cross-section view thereof on line 9—9 in FIG. 2;

FIG. 10 is a top and side perspective view of a second embodiment thereof;

FIG. 11 is a top plan view of the second embodiment;

FIG. 12 is a bottom plan view of the second embodiment;

FIG. 13 is a side elevation view of the second embodiment, the opposite side elevation being a mirror image;



FIG. 14 is a front elevation view of the second embodiment;

FIG. 15 is a rear elevation view of the second embodiment;

FIG. 16 is an exploded side elevation view of the second embodiment;

FIG. 17 is a cross-section view of the second embodiment taken on line 17—17 in FIG. 11; and,

FIG. 18 is a cross-section view of the second embodiment taken on line 18—18 in FIG. 11.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 14




FIG. 13

