



US00D350420S

United States Patent [19]
Cudney et al.

[11] **Patent Number: Des. 350,420**

[45] **Date of Patent: ** Sep. 6, 1994**

[54] **SADDLE PAD**

[75] **Inventors: Douglas J. Cudney; Karen E. Breitbach, both of Orangeville, Canada**

[73] **Assignee: Tipperary Sport Products, Inc., Orangeville, Canada**

[**] **Term: 14 Years**

[21] **Appl. No.: 7,850**

[22] **Filed: May 4, 1993**

[52] **U.S. Cl. D30/135**

[58] **Field of Search 54/44.1, 44.5, 65-66; D30/134-135**

[56] **References Cited**

U.S. PATENT DOCUMENTS

568,474	9/1896	Clark .	
595,111	12/1897	Perry	54/66
709,930	9/1902	Rensman	54/66
1,824,488	9/1931	Kopf	54/66
2,072,188	3/1937	Tauber	54/66
3,323,287	6/1967	Hilmer	54/66
4,136,506	1/1979	Miller	54/66
4,242,769	1/1981	Rayfield et al.	2/79
4,471,538	9/1984	Pomeranz et al.	54/44.1
4,683,709	8/1987	Vasko et al.	54/66
4,695,496	9/1987	Lee	54/66
4,800,709	1/1989	Le Tixerant	54/66
4,827,701	5/1989	Gonzales	54/66
4,974,397	12/1990	Ricken	54/66
5,038,551	8/1991	Farmer	54/66
5,058,367	10/1991	Evertson	54/66
5,059,467	10/1991	Berkovitz	2/2.5
5,175,986	1/1993	Farley	54/44.1

FOREIGN PATENT DOCUMENTS

2428852	1/1976	Fed. Rep. of Germany	54/66
12291	8/1854	France	54/44.1
323779	8/1902	France	54/44.1
328828	7/1903	France	54/44.1
624297	7/1927	France	54/44.5
1047693	12/1953	France	54/44.1
2495124	6/1982	France	54/66
14898	of 1887	United Kingdom	54/44.1
10621	of 1889	United Kingdom	54/44.1
19335	of 1900	United Kingdom .	
426078	3/1935	United Kingdom	54/66
1403896	8/1975	United Kingdom	54/44.1
2090512	7/1982	United Kingdom	54/66

OTHER PUBLICATIONS

Gayer's Inc., Catalog; p. 1; Double Fleece Pad (top right corner).
Jabez Cliff & Comp., Ltd. Catalog of English Saddlery; p. 19; No. 3260; Saddle Numnah.
Crump Saddlery Company, Inc. Catalog; p. 15; Pads.
Miller's Catalog; p. 92 #B-Saddle Pad; & p. 77-#A Countour Saddle Pad.



Primary Examiner—CathyAnne MacCormac
Attorney, Agent, or Firm—David H. Semmes

[57] **CLAIM**

The ornamental design for a saddle pad, as shown and described.

DESCRIPTION

FIG. 1 is a side elevation of a saddle pad, embodying our new design;
FIG. 2 is a top plan;
FIG. 3 is a bottom plan;
FIG. 4 is a front elevation;
FIG. 5 is a rear elevation; and,
FIG. 6 is a fragmentary section, taken along section lines 6—6 of FIG. 1.






FIG. 1




FIG. 2




FIG. 3




FIG. 6




FIG. 4




FIG. 5