



US00D350905S

United States Patent [19]

[11] Patent Number: **Des. 350,905**

Kiernicki

[45] Date of Patent: **** Sep. 27, 1994**

[54] FUSE CONDITION INDICATOR

D. 297,516	9/1988	Wang	D10/77
2,229,009	1/1941	Berry	D10/77
4,998,067	3/1991	Puckett et al.	340/638 X

[76] Inventor: **Lorenz S. Kiernicki**, 21 Princeway Drive, St. Catharines, Ontario, Canada, L2N-2X7

Primary Examiner—Alan P. Douglas
Assistant Examiner—Antoine D. Davis
Attorney, Agent, or Firm—Hugh E. Smith

[**] Term: **14 Years**

[57] **CLAIM**

[21] Appl. No.: **5,103**

The ornamental design for a fuse condition indicator, as shown and described.

[22] Filed: **Feb. 8, 1993**

[52] U.S. Cl. **D10/77; D10/78**

[58] Field of Search 73/5, 481; 324/114, 324/115, 424, 503, 504, 550; 340/638, 639, 691, 693; D10/77, 78

DESCRIPTION

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 196,238	9/1963	Johnson	D10/77
D. 252,502	7/1979	Kelly, III	D10/77
D. 273,580	4/1984	Riumbau	D10/77 X

FIG. 1 is a front elevational view of the fuse condition indicator showing my new design; FIG. 2 is a rear elevational view thereof; FIG. 3 is a left side elevational view thereof; FIG. 4 is a right side elevational view thereof; FIG. 5 is a top plan view thereof; FIG. 6 is a bottom plan view thereof; and, FIG. 7 is an isometric view thereof.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

