



US00D350929S

**United States Patent** [19]  
**Attinello et al.**

[11] **Patent Number: Des. 350,929**  
[45] **Date of Patent: \*\* Sep. 27, 1994**

[54] **TIRE TREAD**

[75] **Inventors:** John S. Attinello, Hartville; Norman D. Anderson; Samuel P. Landers, both of Uniontown; Dale G. Freygang, Akron, all of Ohio

[73] **Assignee:** The Goodyear Tire & Rubber Company, Akron, Ohio

[\*\*] **Term:** 14 Years

[21] **Appl. No.:** 6,828

[22] **Filed:** Apr. 8, 1993

[52] **U.S. Cl.** ..... D12/147

[58] **Field of Search** ..... 152/209 R, 209 B, 209 D; D12/136, 140, 141-143, 146-151

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

D. 338,179 8/1993 Miller et al. .... D12/147  
5,137,068 8/1992 Loidl et al. .... D12/147

**OTHER PUBLICATIONS**

1992 Tread Design Guide, p. 73, Sumitomo HTR 70 (HR Rated) Tire, bottom right side of page.


*Primary Examiner*—James M. Gandy  
*Attorney, Agent, or Firm*—T. P. Lewandowski

[57] **CLAIM**

The ornamental design for a tire tread, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of a tire tread showing our new design it being understood that the pattern is repeated throughout the circumference thereof; FIG. 2 is a front elevational view thereof; FIG. 3 is a side elevational view thereof; and, FIG. 4 is an enlarged fragmentary front view thereof. In the drawings, the broken line showing of the tire sidewall and the solid line defining the peripheral boundary between the tire tread and the sidewall are for illustrative purposes only and form no part of the claimed design.








FIG-1




FIG-2






FIG-3




FIG-4