



US00D352221S

United States Patent [19]

Scholl

[11] Patent Number: Des. 352,221
[45] Date of Patent: ** Nov. 8, 1994

[54] EXIT OPERATOR

[76] Inventor: Winfried Scholl, Ikenstr. 21, D-4000
Düsseldorf, Germany

[**] Term: 14 Years

[21] Appl. No.: 916,175

[22] Filed: Jul. 17, 1992

[30] Foreign Application Priority Data

Jan. 17, 1992 [DE] Germany M9200278.1
[52] U.S. Cl. D8/315; D8/320
[58] Field of Search D8/300, 301, 302, 315-320;
70/92; 292/92, 93, DIG. 65

[56] References Cited

U.S. PATENT DOCUMENTS

2,426,041 8/1947 Moorhouse 292/93
3,104,539 9/1963 Cutler 70/92
4,895,399 1/1990 Horgan, Jr. 292/92

OTHER PUBLICATIONS

HEWI Inc. Cat.; effective date Jan. 1982; p. 100.12a;
handle 550.40.360.
HEWI Inc. Cat., effective date Jan. 1982; p. 100.12a;
handle 550.40 gk.

Primary Examiner—B. J. Bullock
Attorney, Agent, or Firm—Michael J. Striker

[57] CLAIM

The ornamental design for an exit operator, as shown
and described.

DESCRIPTION

FIG. 1 is a perspective view of an exit operator showing
my new design;
FIG. 2 is a front view thereof, the rear being unorna-
mented;

FIG. 3 is a left side view thereof, the right side being
substantially a mirror image;
FIG. 4 is top plan view thereof;
FIG. 5 is a perspective view of a second embodiment of
the design of FIG. 1, the only difference being the ar-
rangement of the upper fastening element;
FIG. 6 is a front view thereof;
FIG. 7 is a left side view thereof;
FIG. 8 is a top plan view thereof;
FIG. 9 is a perspective view of a third embodiment of
the design of FIG. 1, the only difference being the con-
figuration of the handle;
FIG. 10 is a perspective view of a fourth embodiment of
the design of FIG. 1, the only difference being the con-
figuration of the handle;
FIG. 11 is a perspective view of a fifth embodiment of
the design of FIG. 1, the only difference being the con-
figuration of the handle;
FIG. 12 is a perspective view of the lower fastening
element shown separately for clarity of illustration;
FIG. 13 is a right side view of FIG. 12;
FIG. 14 is a front view of FIG. 12, the rear being unor-
namented;
FIG. 15 is a left side view of FIG. 12;
FIG. 16 is a bottom view of FIG. 12;
FIG. 17 is a top view of FIG. 12;
FIG. 18 is a perspective view of the upper fastening
element shown separately for clarity of illustration;
FIG. 19 is a front view of FIG. 18, the rear being
unornamented;
FIG. 20 is a left side view of FIG. 18, the right being
substantially a mirror image;
FIG. 21 is a bottom view of FIG. 18;
FIG. 22 is a top view of FIG. 18;
FIG. 23 is a perspective view of the second embodiment
of the upper fastening element as shown in FIG. 5;
FIG. 24 is a front view of FIG. 23, the rear being unor-
namented;
FIG. 25 is a left side view of FIG. 23, the right side
being substantially a mirror image;
FIG. 26 is a bottom view of FIG. 23; and,
FIG. 27 is a top view of FIG. 23.




Fig.1




Fig.2



Fig.3





Fig.4.









Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16'




Fig. 17



Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig.23.




Fig.24




Fig. 25




Fig. 26.




Fig.27.

