



US00D352358S

United States Patent [19]

Yan

[11] Patent Number: **Des. 352,358**

[45] Date of Patent: **** Nov. 8, 1994**

[54] **LOW CURRENT MESSAGE UNIT**

[76] Inventor: **Lai Y. Yan**, 13409 Burton St.,
Panorama City, Calif. 91402

[**] Term: **14 Years**

[21] Appl. No.: **6,314**

[22] Filed: **Mar. 25, 1993**

[52] U.S. Cl. **D24/200; D24/170;**
D24/186

[58] Field of Search 128/24.1, 24.5, 36,
128/32; D24/200, 186, 170, 165

D. 299,747 2/1989 Wilson et al. D24/100
3,996,929 12/1976 Mabuchi 128/36 X
4,052,981 10/1977 Bachmann 128/36
4,098,266 7/1978 Muchiski et al. 128/36

Primary Examiner—Stella Reid
Attorney, Agent, or Firm—Roger A. Marrs

[57] CLAIM


The ornamental design for a low current message unit, as shown.

DESCRIPTION

FIG. 1 is a front elevational view of a low current message unit showing my new design;
FIG. 2 is a rear view thereof;
FIG. 3 is a side view thereof with its opposite side being a mirror image thereof;
FIG. 4 is a top plan view thereof; and,
FIG. 5 is a bottom view thereof.

[56] **References Cited**
U.S. PATENT DOCUMENTS

D. 192,841 5/1962 Moss et al. D24/200
D. 250,480 12/1978 Wetterman et al. D24/170






FIG. 1.




FIG. 2.




FIG. 3.




FIG. 4.




FIG. 5.