



US00D353556S

United States Patent [19]

[11] Patent Number: **Des. 353,556**

Chia et al.

[45] Date of Patent: **** Dec. 20, 1994**

- [54] **JEWELRY ROPE CHAIN SPIRAL COMPONENT**
- [76] Inventors: **Meang Chia; Cheo Chia**, both of Chain & Charm Manufacturers, 412 W. 6th St., Suite #1104, Los Angeles, Calif. 90014
- [**] Term: **14 Years**
- [21] Appl. No.: **685,570**
- [22] Filed: **Apr. 12, 1991**
- [52] U.S. Cl. **D11/93; D11/12**
- [58] Field of Search **59/78-92; 63/1.1-11; D11/1-18, 93-94**

- Exhibit 10—Michael Antohon ad (1990-1991).
- Exhibit 13—King Fook Gold ad (Hong Kong Jewelry Review 1991).
- Exhibit 14—Ring International ad (Hong Kong Jewelry Review 1991).
- Exhibit 19—William Pitt ad (1991).

Primary Examiner—Ralf T. Seifert
Attorney, Agent, or Firm—Ladas & Parry

[57] CLAIM

The ornamental design for a jewelry rope chain spiral component, as shown and described above.

[56] References Cited

DESCRIPTION

U.S. PATENT DOCUMENTS


D. 27,087	5/1897	Edge .	
D. 89,801	5/1933	Speidel .	
D. 138,043	6/1944	Page	D11/23
D. 142,939	11/1945	Benbow .	
D. 160,974	11/1950	Schraysshuen	D11/79
D. 170,848	11/1953	Boucher	D11/18
D. 173,239	10/1954	Philippe .	
D. 174,264	3/1955	Katz .	
D. 174,567	4/1955	Katz	D11/17
D. 175,510	9/1955	Katz .	
D. 175,875	10/1955	Armbrust .	
D. 175,876	10/1955	Armbrust .	
D. 202,284	9/1965	Hartman	D11/17
D. 237,732	11/1975	Roberts	D11/79
D. 265,728	8/1982	Bales .	
D. 277,369	1/1985	Otake .	
D. 301,698	6/1989	Markovits .	
D. 301,699	6/1989	Markovits .	
2,801,565	8/1957	Nicollet .	

OTHER PUBLICATIONS

- Exhibit 2—Nobe Shoten Co. ad (1987).
- Exhibit 3—Pigeon Jewelry Co. ad (1987).
- Exhibit 4—Urban Gold ad (1987).
- Exhibit 5—Hosaka Jewelry ad (1987).
- Exhibit 6—Hiai Necklace Industry Co. ad (1987).
- Exhibit 8—Jerry Madison ad (in Jun. 1989 issue of the Goldsmith).
- Exhibit 9—Dolan Bullock ad (in Jun. 1989 issue of the Goldsmith).

FIG. 1 is a perspective view of a first embodiment of my new design for a jewelry rope chain spiral component; FIG. 2 is a front view of the first embodiment of my new design, to which a rear view also corresponds; FIG. 3 is a right side view of the first embodiment of my new design; FIG. 4 is a top end view of the first embodiment of my new design; FIG. 5 is a bottom view of the first embodiment of my new design; FIG. 6 is a right side view of the second embodiment of my new design wherein the spiral is in a direction opposite to that depicted in FIGS. 1-5 and wherein the views corresponding to those depicted in FIGS. 1-5 are mirror images of those views. FIG. 7 is a perspective view of a third embodiment of my new design for a jewelry rope chain spiral component; FIG. 8 is a front view of the third embodiment of my new design, to which a rear view also corresponds; FIG. 9 is a right side view of the third embodiment of my new design; FIG. 10 is a top end view of the third embodiment of my new design; FIG. 11 is a bottom end view of the third embodiment of my new design; FIG. 12 is front view of a fourth embodiment of my new design wherein the spiral is in a direction opposite

(Description continued on next page.)



DESCRIPTION

to that depicted in FIGS. 7-11 and wherein the views corresponding to those depicted in FIGS. 7-12 are mirror images of those views;

FIG. 13 is a perspective view of a fifth embodiment of my design for a jewelry rope chain spiral component;

FIG. 14 is a front view of the fifth embodiment of my new design, to which the rear view corresponds;

FIG. 15 is a right side view of the fifth embodiment of my new design;

FIG. 16 is a top end view of the fifth embodiment of my new design;

FIG. 17 is a bottom end view of the fifth embodiment of my design;

FIG. 18 is a front view of a sixth embodiment of my new design wherein the spiral is in a direction opposite to that depicted in FIGS. 13-17 and wherein views corresponding to those depicted in FIGS. 13-17 are mirror images of those views;

FIG. 19 is a perspective view of a seventh embodiment

of my new design for a jewelry rope chain spiral component;

FIG. 20 is a front view of the seventh embodiment of my new design, to which a rear view corresponds;

FIG. 21 is a right side view of the seventh embodiment of my new design;

FIG. 22 is a top end view of the seventh embodiment;







FIG. 23 is a bottom end view of the seventh embodiment;

FIG. 24 is a front view of an eighth embodiment of my new design for a jewelry rope chain spiral component wherein the spiral is in a direction opposite to that depicted in FIGS. 19-23 and wherein views corresponding to those depicted in FIGS. 19-23 are mirror images of those views;

FIG. 25 is a view of the first embodiment in a position of use; and,

FIG. 26 is a view of the fifth embodiment shown in a position of use.

The broken line showing of a partial jewelry chain in FIGS. 25 and 26 is for illustrative purposes only and forms no part of the claimed design.






FIG. 7




FIG. 8

FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 18




FIG. 17




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 24




FIG. 23




FIG. 25




FIG. 26

