



US00D354811S

# United States Patent [19]

[11] Patent Number: **Des. 354,811**

**Tsushi**

[45] Date of Patent: **\*\* Jan. 24, 1995**

[54] **COMBINED PULSIMETER AND CORD**

4,301,808 11/1981 Taus ..... 128/687

[75] Inventor: **Masao Tsushi, Osaka, Japan**

*Primary Examiner*—A. Hugo Word

[73] Assignee: **Cateye Co., Ltd., Osaka, Japan**

*Assistant Examiner*—Eric M. Watterson

[\*\*] Term: **14 Years**

*Attorney, Agent, or Firm*—Allegretti & Witcoff, Ltd.

[21] Appl. No.: **921,512**

[57] **CLAIM**

[22] Filed: **Jul. 29, 1992**

The ornamental design for a combined pulsometer and cord, as shown and described.

[30] **Foreign Application Priority Data**

**DESCRIPTION**

Jan. 31, 1992 [JP] Japan ..... 4-2668

FIG. 1 is a front view of the combined pulsometer and cord shown in FIG. 8 with the cord portion omitted.

[52] U.S. Cl. .... **D24/165**

FIG. 2 is a rear view of the combined pulsometer and cord shown in FIG. 9 with the cord and belt clip omitted;

[58] Field of Search ..... D24/165, 167, 169, 186;  
D10/30, 31, 32, 38, 90; 128/687, 672, 667, 680,  
689, 690

FIG. 3 is a top view thereof;

[56] **References Cited**

FIG. 4 is a bottom view thereof;

**U.S. PATENT DOCUMENTS**

FIG. 5 is a left side view thereof;

D. 262,488 12/1981 Rossman et al. .... D24/165

FIG. 6 is a right side view thereof;

D. 263,740 4/1982 Rosers et al. .... D24/167

FIG. 7 is a perspective view thereof;

D. 288,297 2/1987 Chou ..... D10/30

FIG. 8 is a front perspective view of the combined pulsometer and cord showing my new design; and,

D. 293,715 1/1988 Krasnow ..... D24/169

FIG. 9 is a rear perspective view thereof.




FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG. 7




FIG. 8




FIG. 9

