



US00D355180S

United States Patent [19]

[11] Patent Number: **Des. 355,180**

Zander

[45] Date of Patent: **** Feb. 7, 1995**

[54] **FILM CASSETTE WITH EXPOSURE STATUS INDICATORS**

5,106,030	4/1992	Pagano et al.	242/71.1
5,115,268	5/1992	Kitagawa et al.	354/275
5,234,175	8/1993	Pagano	242/71.1

[75] Inventor: **Dennis R. Zander**, Penfield, N.Y.

Primary Examiner—Theodore M. Shooman
Attorney, Agent, or Firm—Roger A. Fields

[73] Assignee: **Eastman Kodak Company**, Rochester, N.Y.

[57] **CLAIM**

[**] Term: **14 Years**

The ornamental design for a film cassette with exposure status indicators, as shown and described.

[21] Appl. No.: **8,735**

DESCRIPTION

[22] Filed: **May 20, 1993**

[52] U.S. Cl. **D14/121**

FIG. 1 is a right-side, bottom, front perspective view of a film cassette with exposure status indicators, showing my new design;

[58] Field of Search **D14/120-123, D14/299; 242/71.1, 71.9; 354/275; D9/424**

FIG. 2 is a left-side, top, rear perspective view thereof;

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 330,549	10/1992	Takahashi	D14/121
D. 342,673	12/1993	Kataoka et al.	D14/121 X
2,072,625	3/1937	Rose	D14/121 X
4,978,985	12/1990	Smart et al.	354/275

FIG. 3 is a front elevation view thereof;



FIG. 4 is a rear elevation view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a bottom plan view thereof;

FIG. 7 is a right-side elevation view thereof; and,

FIG. 8 is a left-side elevation view thereof.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8