

US00D355214S

United States Patent [19]

Menahem

[11] Patent Number: Des. 355,214

[45] Date of Patent: ** Feb. 7, 1995

[54]	MULTIPLE RING BINDER		
[75]	Inventor:	Salomon Menahem, Hadera, Israel	
[73]	Assignee:	Superfile Ltd., Hadera-Karkur, Israel	
[**]	Term:	14 Years	
[21]	Appl. No.:	869,635	
[52]	U.S. Cl	Apr. 16, 1992 D19/27	
[58]	Field of Search		
		56, 80 R, 72	

[56] References Cited

U.S. PATENT DOCUMENTS

642,244	1/1900	Morehouse 402/73
•		Mudd 281/21.1 X
3,618,241	2/1969	Doty et al 281/334
4,722,628	2/1988	Rager 402/75
4,943,177	7/1990	Jordan et al 402/80 R X

Primary Examiner—Wallace R. Burke
Assistant Examiner—Pamela Burgess
Attorney, Agent, or Firm—Pollock, Vande Sande & Priddy

[57] CLAIM

The ornamental design for a multiple ring binder, as shown and described.

DESCRIPTION

FIG. 1 is a top perspective view of a multiple ring binder showing my new design in a closed position; FIG. 2 is a top perspective view thereof with the cover opened to the first ring binder;

FIG. 3 is a top perspective view thereof with the covers opened to the second ring binder;

FIG. 4 is a top perspective view thereof with the covers opened to the third ring binder;

FIG. 5 is a top perspective view thereof with the covers opened to the fourth ring binders;

FIG. 6 is a front elevational view thereof in a closed position, the undisclosed rear being the same;

FIG. 7 is a right side elevational view thereof;

FIG. 8 is a left side elevational view thereof;

FIG. 9 is a bottom plan view thereof;

FIG. 10 is a top perspective view of a second embodiment of FIG. 1 showing a multiple ring binder in a closed position;

FIG. 11 is a top perspective view thereof with the cover opened to the first ring binder;

FIG. 12 is a top perspective view thereof with the covers opened to the second ring binder;

FIG. 13 is a top perspective view thereof with the covers opened to the third ring binder;

FIG. 14 is a front elevational view thereof in a closed position, the undisclosed rear being the same;

FIG. 15 is a right side elevational view thereof;

FIG. 16 is a left side elevational view thereof;

FIG. 17 is a bottom plan view thereof;

FIG. 18 is a top perspective view of a third embodiment of FIG. 1 showing a multiple ring binder in a closed position;

FIG. 19 is a top perspective view thereof with the cover opened to the first ring binder;

FIG. 20 is a top perspective view thereof with the covers opened to the second ring binder;


FIG. 21 is a front elevational view thereof in a closed position, the undisclosed rear being the same;


FIG. 22 is a right side elevational view thereof;

FIG. 23 is a left side elevational view thereof;

FIG. 24 is a bottom plan view thereof; and,


FIG. 25 is a top perspective view thereof of a fourth embodiment of FIG. 1 showing a multiple ring binder with the cover opened to the first ring binder, it being understood that the only difference from embodiment 1 resides in the number of ring binder retainer rings.






F/G. 1


F/G. 2




F/G. 3



F/G. 4



F/G. 5



F/G. 6







FIG. 7




F/G. 8




F/G. 9




F/G. 10




F/G. 11




F/G. 12




F/G. 13




F/G. 14



F/G. 15




F/G. 16




F/G. 17


Feb. 7, 1995




F/G. 18



F/G. 19



F/G. 20



F/G. 21





FIG. 22 FIG. 23

F/G. 24



F/G. 25