



US00D355298S

United States Patent [19]

[11] Patent Number: **Des. 355,298**

Beger

[45] Date of Patent: **** Feb. 14, 1995**

[54] **RECEPTACLE**

[76] Inventor: **Udo Beger**, Oberndorfer Strasse 24a - 26a, 8300 Landshut, Germany

[**] Term: **14 Years**

[21] Appl. No.: **3,445**

[22] Filed: **Jan. 5, 1993**

[52] U.S. Cl. **D3/244**

[58] Field of Search **D3/244, 284, 303, 305; 190/1; 383/4, 72**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 128,122	7/1941	Lewis	D3/244
D. 164,623	9/1951	Chandlee	D3/244
D. 167,959	10/1952	Stucker	D3/244
D. 220,733	5/1971	Niblack	D3/244
D. 341,934	12/1993	Abraham	D3/244 X
977,129	11/1910	Reynolds	383/4 X
2,731,997	1/1956	Muth et al.	383/72 X
5,187,823	2/1993	Ferguson et al.	383/4 X

FOREIGN PATENT DOCUMENTS

273619 10/1913 Germany 383/4



Primary Examiner—Louis S. Zarfaz
Attorney, Agent, or Firm—Harris, Tucker & Hardin

[57] **CLAIM**

The ornamental design of a receptacle, as shown and described.

DESCRIPTION

FIG. 1 is a perspective oblique view from above of the receptacle in its closed state;
 FIG. 2 is a perspective oblique view from above of the receptacle in its partly opened state;
 FIG. 3 is a perspective oblique view from above of the receptacle in an entirely unfolded state, the inner side of said receptacle forming a support surface;
 FIG. 4 is a perspective oblique view from above of the receptacle in a partly closed state, with holding straps being disposed inside the receptacle which could serve to hold utensils therein;
 FIG. 5 is a side view of the receptacle in its closed state;
 FIG. 6 is a top view of the receptacle in its closed state;
 and,
 FIG. 7 is a bottom view of the receptacle in its closed state.






FIG.1




FIG. 2




FIG. 3




FIG.4




FIG. 5




FIG. 6




FIG.7