



US00D356520S

United States Patent [19] Bartky

[11] Patent Number: **Des. 356,520**
[45] Date of Patent: **** Mar. 21, 1995**

[54] **CARDIOID JEWELRY CORD FASTENER**

[75] Inventor: **W. Scott Bartky, Chicago, Ill.**

[73] Assignee: **Ari Imports, Inc., Chicago, Ill.**

[**] Term: **14 Years**

[21] Appl. No.: **25,777**

[22] Filed: **Jul. 11, 1994**

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 187,709, Jan. 27, 1994, which is a continuation-in-part of Ser. No. 3,321, Jan. 12, 1993, abandoned.

[52] U.S. Cl. **D11/87**

[58] Field of Search **D8/382, 356; 29/518; 72/410; 7/134; D11/86-88, 200-206, 1-19, 215; 59/79.1; 24/50, 129 R, 130, 129 D, 129 W, 115 R, 326**

[56] **References Cited**

U.S. PATENT DOCUMENTS

229,257	6/1880	King	D11/87
777,412	12/1904	Hamel et al.	.	
785,522	12/1930	Matthes	24/115 R
1,955,005	4/1934	Maloney	24/115 R
2,327,683	8/1943	Warner et al.	29/518
2,461,030	2/1949	Brickman	29/518
2,583,625	1/1952	Bergan	.	
2,731,862	1/1956	Schinske	.	
2,763,171	9/1956	Modrey et al.	72/410
2,845,670	8/1958	Brown et al.	D11/212
2,975,425	3/1961	Diehm et al.	29/518
3,020,333	2/1962	Bangert et al.	29/518
3,094,755	6/1963	Casanave	24/129 R
3,175,281	3/1965	Elfsten	.	
3,259,966	7/1966	Canter	.	
3,396,571	8/1968	Porter	.	
4,009,514	3/1977	Couto	.	
4,219,919	9/1980	Fischbein et al.	.	
4,529,240	7/1985	Engel	24/129 R
4,637,084	1/1987	Wood	.	
4,662,056	5/1987	Becker	24/129 W

4,738,006	4/1988	Juarez	24/129 W X
4,955,750	9/1990	Goran	24/115 R X
5,020,192	6/1991	Gerlach	24/129 R X
5,042,285	8/1991	Levy	.	

FOREIGN PATENT DOCUMENTS

966582	8/1957	Germany	.	
3606429	9/1987	Germany	29/751
423868	7/1947	Italy	72/410
5398	11/1920	Netherlands	72/410

OTHER PUBLICATIONS

Poris, Ruth F., *Step-By-Step Bead Stringing*, Golden Hands Press, pp. 10-13 and 24-25, 1991.

Primary Examiner—Ralf T. Seifert

Attorney, Agent, or Firm—Olson & Hierl, Ltd.

[57] **CLAIM**

The ornamental design for a cardioid jewelry cord fastener, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a cardioid jewelry fastener showing my new design, the broken line showing of partial cords is for illustrative purposes only and forms no part of the claimed design;

FIG. 2 is a top plan view, the opposite side view being a mirror image;

FIG. 3 is a front elevational view;

FIG. 4 is a rear elevational view;

FIG. 5 is a side elevational view, the opposite side view being a mirror image;

FIG. 6 is a perspective view of a cardioid jewelry fastener showing a second embodiment of my new design; FIG. 7 is a top plan view of FIG. 6, the opposite side view being a mirror image;

FIG. 8 is a front elevational view of FIG. 6;

FIG. 9 is a rear elevational view of FIG. 6; and,

FIG. 10 is a side elevational view of the FIG. 6, the opposite side view being a mirror image.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8



FIG. 9




FIG. 10

