



US00D357722S

United States Patent [19]

Fireman

[11] Patent Number: **Des. 357,722**

[45] Date of Patent: **** Apr. 25, 1995**

[54] **ARM FLOAT**

[75] Inventor: **Andrew F. Fireman**, Newton Upper Falls, Mass.

[73] Assignee: **Aqua-Leisure Industries, Inc.**, Avon, Mass.

[**] Term: **14 Years**

[21] Appl. No.: **18,351**

[22] Filed: **Feb. 4, 1994**

[52] U.S. Cl. **D21/238; D21/237**

[58] Field of Search **D21/237, 238; 441/122, 441/113, 123, 59, 106, 112, 80, 81**

[56] **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|------------|---------|--------------------|---------|
| D. 205,327 | 7/1966 | Lukas | D21/238 |
| D. 321,742 | 11/1991 | Yu | D21/237 |
| 1,611,427 | 12/1926 | Evans . | |
| 2,111,358 | 3/1938 | Crockett | 9/20 |
| 3,296,636 | 1/1967 | Markwitz | 9/340 |
| 3,332,415 | 7/1967 | Ericson | 128/87 |
| 3,727,252 | 4/1973 | Bauermeister | 9/344 |
| 3,775,788 | 12/1973 | Markwitz | 9/344 |
| 3,820,179 | 6/1974 | Maertin | 9/344 |
| 3,835,493 | 9/1974 | Grivna | 9/307 |
| 3,987,506 | 10/1976 | Markwitz | 5/338 |
| 4,671,507 | 6/1987 | Huttner | 272/71 |
| 4,804,326 | 2/1989 | Lennon | 434/254 |
| 4,813,899 | 3/1989 | Fujimoto | 441/122 |
| 4,905,991 | 3/1990 | Alston | 272/119 |
| 4,936,806 | 6/1990 | Rudy | 441/122 |
| 5,037,341 | 8/1991 | Howard | 441/89 |
| 5,060,661 | 10/1991 | Howard | 128/845 |

5,190,489 3/1993 Yeung 441/122

FOREIGN PATENT DOCUMENTS

| | | |
|---------|--------|------------------|
| 3336300 | 5/1985 | Germany . |
| 2-68295 | 3/1990 | Japan . |
| 2090792 | 7/1982 | United Kingdom . |
| 2108053 | 5/1983 | United Kingdom . |
| 2193691 | 2/1988 | United Kingdom . |



Primary Examiner—Kay H. Chin
Attorney, Agent, or Firm—Wolf, Greenfield & Sacks

[57] CLAIM

The ornamental design of an arm float, as shown and described.

DESCRIPTION

FIG. 1 is a left rear perspective view of one embodiment of an arm float, showing a new design; FIG. 2 is a right side perspective view thereof; FIG. 3 is a rear elevational view thereof; FIG. 4 is a front elevational view thereof; FIG. 5 is a right side elevational view thereof, with the left side elevation being a mirror image; FIG. 6 is a top plan view thereof, with the bottom plan view being a mirror image; FIG. 7 is a right side perspective view of a second embodiment of an arm float, showing a new design; FIG. 8 is a left side elevational view thereof, with the right side elevation being a mirror image; FIG. 9 is a right front perspective view thereof; FIG. 10 is a front elevational view thereof; FIG. 11 is a rear elevational view thereof; and, FIG. 12 is a top plan view thereof, with the bottom plan view being a mirror image.






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12