



US00D357760S

United States Patent [19]

Osiecki et al.

[11] Patent Number: Des. 357,760
[45] Date of Patent: ** Apr. 25, 1995

[54] FLASHLIGHT

[75] Inventors: Scott W. Osiecki, Skaneateles; Richard H. Chapman, Camillus; Martin S. Clegg, Skaneateles, all of N.Y.
[73] Assignee: Eveready Battery Company, Inc., St. Louis, Mo.
[**] Term: 14 Years
[21] Appl. No.: 6,765
[22] Filed: Apr. 6, 1993
[52] U.S. Cl. D26/49
[58] Field of Search D26/37-50; 362/157, 158, 183, 184, 188-203

[56] References Cited

U.S. PATENT DOCUMENTS

D. 300,667 4/1989 Ohashi D26/49
D. 315,219 3/1991 Brinkmann et al. D26/49
D. 331,118 11/1992 Yeung D26/49


Primary Examiner—Susan J. Lucas
Attorney, Agent, or Firm—Robert W. Welsh


[57] CLAIM

The ornamental design for the flashlight, as shown and described.

DESCRIPTION

FIG. 1 is a oblique view of a first embodiment of the invention;
FIG. 2 is a side elevation view of the invention;
FIG. 3 is a side elevation view of the invention taken at a right angle to that shown in FIG. 2;
FIG. 4 is a side elevation view of the invention from a side opposite that shown in FIG. 2;
FIG. 5 is a front elevational view of the invention;
FIG. 6 is a rear elevational view of the invention;
FIG. 7 is an oblique view of a second embodiment of the invention;
FIG. 8 is a side elevation view of the invention;
FIG. 9 is a side elevation view of the invention taken at a right angle to that shown in FIG. 8;
FIG. 10 is a side elevation view of the invention from a side opposite that shown in FIG. 8;
FIG. 11 is a front elevational view of the invention;
FIG. 12 is a rear elevational view of the invention;
FIG. 13 is a oblique view of a third embodiment of the invention;
FIG. 14 is a side elevation view of the invention;
FIG. 15 is a side elevation view of the invention taken at a right angle to that shown in FIG. 14;
FIG. 16 is a side elevation view of the invention from a side opposite that shown in FIG. 14;
FIG. 17 is a front elevational view of the invention;
FIG. 18 is a rear elevational view of the invention; and,
FIG. 19 is a perspective view of the flashlight head common to each of the embodiments shown in FIGS. 1-18.








Fig. 2







Fig. 6

*Fig. 3**Fig. 4**Fig. 5*






Fig. 7

*Fig. 8**Fig. 12*




Fig. 9




Fig. 10




Fig. 11




Fig. 13




Fig. 14




Fig. 18




Fig. 15

Fig. 16





Fig. 17