

US00D357942S

United States Patent [19]

Louis-Seize

[11] Patent Number: Des. 357,942

[45] Date of Patent: ** May 2, 1995

| [54] | ILLUMINABLE SIGN POST | | | |
|--|-----------------------|--|--|--|
| [75] | Inventor: | Denis Louis-Seize, Clarence Creek, Canada | | |
| [73] | Assignee: | Louis-XVI Signs, Clarence Creek, Canada | | |
| [**] | Term: | 14 Years | | |
| [21] | Appl. No.: | 12,963 | | |
| [22] | Filed: | Sep. 14, 1993 | | |
| [30] Foreign Application Priority Data | | | | |
| Mar. 18, 1993 [CA] Canada | | | | |

| Mar | . 18, 1993 [CA] | Canada |
|------|-----------------|---------------------------------------|
| [52] | U.S. Cl | D20/10; D25/126 |
| [58] | Field of Search | |
| | D20/41; 40/ | 1, 540, 541, 542, 557, 558, 560, 561, |

562, 563, 564, 584, 591, 592, 593, 624; D25/126

[56] References Cited

U.S. PATENT DOCUMENTS

| D. 275,969 | 10/1984 | Bowers |
|------------|---------|------------------------|
| D. 317,790 | 1/1991 | Hey D20/10 |
| D. 338,042 | 8/1993 | Giammanco |
| 1,592,595 | 7/1926 | Arendt 40/564 |
| 1,663,386 | 3/1928 | Rice 40/564 |
| 2,156,553 | 5/1939 | Vendope 40/558 |
| 2,260,082 | 10/1941 | McCauley 40/564 |
| 2,677,908 | 5/1954 | Clevenger et al 40/563 |
| 3,587,185 | 6/1971 | Deal 40/564 |

Primary Examiner—Wallace Burke
Assistant Examiner—Marcus Jackson
Attorney, Agent, or Firm—Dickinson, Wright, Moon,
Van Dusen & Freeman

[57] CLAIM

The ornamental design for a illuminable sign post, as shown and described.

DESCRIPTION

FIG. 1 is a top view of a first embodiment of my design;

FIG. 2 is a bottom view of said first embodiment;

FIG. 3 is a front view of said first embodiment;

FIG. 4 is a back view of said first embodiment;

FIG. 5 is a right side view of said first embodiment;

FIG. 6 is a left side view of said first embodiment;

FIG. 7 is a perspective view of said first embodiment;

FIG. 8 is a perspective view of a second embodiment of my design;

FIG. 9 is a top view of said second embodiment;

FIG. 10 is a perspective view of a third embodiment of my design;

FIG. 11 is a top view of said third embodiment;

FIG. 12 is a perspective view of a fourth embodiment of my design;

FIG. 13 is a top view of said fourth embodiment;

FIG. 14 is a perspective view of a fifth embodiment of my design;

FIG. 15 is a top view of said fifth embodiment;

FIG. 16 is a perspective view of a sixth embodiment of my design;

FIG. 17 is a top view of said sixth embodiment;

FIG. 18 is a perspective view of a seventh embodiment of my design;

FIG. 19 is a top view of said seventh embodiment;

FIG. 20 is a perspective view of an eighth embodiment of my design;

FIG. 21 is a top view of said eighth embodiment;

FIG. 22 is a perspective view of a ninth embodiment of my design;

FIG. 23 is a top view of said ninth embodiment;

FIG. 24 is a perspective view of a tenth embodiment of my design;

FIG. 25 is a top view of said tenth embodiment;

FIG. 26 is a perspective view of an eleventh embodiment of my design;


FIG. 27 is a top view of said eleventh embodiment;

FIG 28 is a perspective view of a twelfth embodiment of my design;

FIG. 29 is a top view of said twelfth embodiment;

FIG. 30 is a perspective view of a thirteenth embodiment of my design; and,

FIG. 31 is a bottom view of said thirteenth embodiment.






FIG.




FIG. 2




FIG. 3








FIG. 4












FIG. 9




FIG. 10






FIG. 11








FIG. 20




FIG. 22




FIG. 21





FIG. 23






FIG. 25




FIG. 26




FIG. 27

