



US00D358707S

United States Patent [19]

[11] Patent Number: **Des. 358,707**

Holt

[45] Date of Patent: **** May 30, 1995**

[54] COMBINED SUNGLASS HOLDER AND INSERT FOR AN AUTOMOBILE LIGHTER RECEPTACLE

[75] Inventor: **Bryan S. Holt**, 2071 C Lake Park Dr., Smyrna, Ga. 30080

[73] Assignee: **Bryan S. Holt**, Smyrna, Ga.

[**] Term: **14 Years**

[21] Appl. No.: **10,761**

[22] Filed: **Jul. 19, 1993**

[52] U.S. Cl. **D3/266; D8/373; D12/400; D27/194**

[58] Field of Search **D13/156; 174/138 F; D9/439; D3/266; D8/373; D27/194; D12/400**

[56] References Cited

U.S. PATENT DOCUMENTS

D. 46,632	11/1914	Eaton	D9/439
D. 256,010	7/1980	Fry	D13/156
D. 316,402	4/1991	Baker	D13/156
D. 338,190	8/1993	Bradbury	D13/156

Primary Examiner—James M. Gandy

Assistant Examiner—Holly Baynham

[57] CLAIM

The ornamental design for a combined sunglasses holder

and insert for an automobile lighter receptacle, as shown.

DESCRIPTION

FIG. 1 is a side elevational view of a combined sunglasses holder and insert for an automobile lighter receptacle showing my new design with the opposite side being a mirror image thereof;

FIG. 2 is a side elevational view thereof of a second embodiment of the design shown in FIG. 1 with the opposite side being a mirror image thereof;

FIG. 3 is a sectional view of both embodiments taken along line 3—3 of FIGS. 1 and 2;

FIG. 4 is a sectional view of both embodiments taken along line 4—4 of FIGS. 1 and 2;

FIG. 5 is top view thereof of the first embodiment of the design shown in FIG. 1;

FIG. 6 is a top view thereof of the second embodiment of the design shown in FIG. 2;

FIG. 7 is a back view thereof of the first embodiment of the design shown in FIG. 1;


FIG. 8 is a back view thereof of the second embodiment of the design shown in FIG. 2;

FIG. 9 is a front view thereof of the first embodiment of the design shown in FIG. 1;

FIG. 10 is a front view thereof of the second embodiment of the design shown in FIG. 2;

FIG. 11 is a bottom view thereof of the first embodiment of the design shown in FIG. 1; and,

FIG. 12 is a bottom view thereof of the second embodiment of the design shown in FIG. 2.






Fig. 1




Fig. 3




Fig. 2




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12