



US00D359479S

# United States Patent [19]

Jondrow et al.

[11] Patent Number: Des. 359,479

[45] Date of Patent: \*\* Jun. 20, 1995

[54] COMPUTER INPUT DEVICE

[75] Inventors: Timothy J. Jondrow; Michael D. Derocher, both of Corvallis, Oreg.

[73] Assignee: Hewlett-Packard Corporation, Palo Alto, Calif.

[\*\*] Term: 14 Years

[21] Appl. No.: 3,560

[22] Filed: Jan. 12, 1993

## Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 856,436, Mar. 23, 1992.

[52] U.S. Cl. .... D14/114

[58] Field of Search ..... D14/114; D13/158; D21/48; 178/18.9; 200/5 R, 5 A, 6 R, 6 A; 213/148 B; 273/148 B; 345/156-167; 364/188-190; 74/471

[56] References Cited

## U.S. PATENT DOCUMENTS

D. 301,142	5/1989	Chu .....	D14/114
D. 302,426	7/1989	Bradley et al. ....	D14/114
D. 331,043	11/1992	Yang .....	D14/114
D. 340,041	10/1993	Kawashima et al. ....	D14/114
D. 340,923	11/1993	Tso .....	D14/114
D. 348,451	7/1994	Tso .....	D14/114
4,680,577	7/1987	Straayer et al. .	
4,782,327	1/1988	Kley et al. .	
4,896,554	1/1990	Culver .	
4,935,728	6/1990	Kley .	
5,049,863	9/1991	Oka .	
5,126,955	6/1992	Tomoda .	

## OTHER PUBLICATIONS

1-Page article entitled "A Different Kind of Animal", ALTRA, circa Jan. 1992.

2-Page brochure entitled "Push-n-Point" Home Row, Inc.; Apr., 1991.

"The Mouse Ran Under The 'J'", Electronic Engineering Times; Jul. 2, 1990.

"Thumb-actuated, Cursor-positioning Devices Provides 2-D Axis Control in a Small Space" ALPS Electric U.S.A., Product Update, EDN, Feb., 1989.

News Release by ALPS Electric (USA), Inc. entitled

"ALPS Electric Introduces New Cursor Control Device for Laptops," released Nov. 14, 1988-2 pages.

"Field Mice, Different, Yes. Better, Maybe"; PC Magazine, Oct. 15, 1991; pp. 111-133.

"Isn't It Time We Get Serious About Laptop Pointing Devices?", Article by John Dickinson; Apr. 1991, p. 46.

"Input Alternatives-Howard and Why to Choose a Better Pointing Device" by Franklin N. Tessler; Macworld, Jun. 1992; pp. 154-159.

"Display-Selection Techniques for Text Manipulation" by William K. English, Douglas C. Engelbart & Melvyn L. Berman; IEEE Transactions on Human Factors in Electronics; Mar. 1967.

"Fingertip Mouse Control Without Leaving Your Keyboard"; May 1991; PC World, p. 103.

"Fresh Ways to TALK to Your Computer", Design News, Feb. 25, 1991, pp. 83-86.

"Touchman-The World's First Stationary Mouse" Agiler, 5-page brochure; Sep. 14, 1990.

"Notebooks Need Portable Pointer-Increasing Importance of Graphical Interface Urges Portables to Comply"; Infoworld; Jun. 17, 1991, p. 21.

"The Twiddler" Handykey Corporation brochure, copyright Jan. 1991.

Pointing Device Specification Sheets, 3 pages-Jun. 3, 1991.

Two page specification sheet, Fujitsu Ltd., Pivoting Dome Pointing Device Jul. 16, 1991.

Micro Track Ball; ALPS Electric Co. Ltd.; 1 page specification, circa Jan. 1992.

Electronics Week, Jul. 13, 1984, p. 26, "Puck Pointer Combines Functions of Mouse and Joystick in Number-Pad Sized Package".


PC Magazine, Aug. 1987, pp. 95-96, 99-101, 105-106, 177-120, 159-161, 183-185, 199-200.

"Lightgate Input Device Offers More Intuitive, Precise Interface" Info-World, Dec. 14, 1987, 2 pages.

Primary Examiner—Melanie H. Tung

[57] CLAIM

The ornamental design for a computer input device, as shown and described.



**DESCRIPTION**

FIG. 1 is a top perspective view of a computer input device showing our new design;

FIG. 2 is a perspective view of the computer input device slightly enlarged as compared to FIG. 1;

FIG. 3 is a left-side elevational view of the computer input device;

FIG. 4 is a right-side elevational view of the computer input device;

FIG. 5 is a top plan view of the computer input device;

FIG. 6 is a bottom plan view of the computer input device;

FIG. 7 is a rear elevational view of the computer input device;

FIG. 8 is a front elevational view of the computer input device;

FIG. 9 is a top perspective view of the computer input device shown in expanded position;

FIG. 10 is a front elevational view of the computer input device;

FIG. 11 is a rear elevational view of the computer input device;

FIG. 12 is a top plan view of the device;

FIG. 13 is a bottom plan view of the computer input device;

FIG. 14 is a left-side elevational view of the computer input device; and,

FIG. 15 is a right-side elevational view of the computer input device.

The extension arm in FIGS. 2, 6-13 is partially shown for ease of illustration. The computer input device is shown in an expanded position in FIGS. 10-15.









FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11






FIG. 12




FIG. 13

FIG. 14




FIG. 15

