



US00D361517S

# United States Patent [19]

[11] Patent Number: **Des. 361,517**

**Petruzzi**

[45] Date of Patent: **\*\* Aug. 22, 1995**

## [54] REPLICA SPICE SHAKER CLOCK

## DESCRIPTION

[76] Inventor: **Thomas G. Petruzzi**, 5118 Belleville Ave., Orlando, Fla. 32812

[\*\*] Term: **14 Years**

[21] Appl. No.: **27,243**

[22] Filed: **Aug. 16, 1994**

[52] U.S. Cl. .... **D10/6; D10/15; D9/509; D14/189**

[58] Field of Search ..... **D10/1-40, D10/122-132; D9/509; D7/629, 612; 368/10, 276-277, 285**

### [56] References Cited

#### U.S. PATENT DOCUMENTS

D. 269,361	6/1983	Marschak	.....	D7/612	X
D. 279,868	7/1985	Boffo	.....	D10/15	X
D. 309,900	8/1990	Illsley	.....	D14/189	X
D. 349,243	8/1994	Hersch	.....	D10/6	X
D. 349,244	8/1994	Hersch	.....	D10/6	X
961,991	6/1910	Ullrich	.....	D9/509	X

*Primary Examiner*—Nelson C. Holtje  
*Attorney, Agent, or Firm*—Allen, Dyer, Doppelt, Franjola & Milbrath

### [57] CLAIM

The ornamental design for a replica spice shaker clock, as shown and described.

FIG. 1 is a top, left perspective view of a replica spice shaker clock showing my new design;  
 FIG. 2 is a top plan view thereof;  
 FIG. 3 is a bottom plan view thereof;  
 FIG. 4 is a right side view thereof, the left side view being a mirror image;  
 FIG. 5 is a front elevational view thereof;  
 FIG. 6 is a rear elevational view thereof;  
 FIG. 7 is a top, left front perspective view thereof with the case in an open position;  
 FIG. 8 is a partial top, left perspective view of a second embodiment of FIG. 1, the only difference being a top element without holes;  
 FIG. 9 is a top plan view of FIG. 8;  
 FIG. 10 is a partial top, left perspective view of a third embodiment of FIG. 1, the only difference being a generally flat top surface;  
 FIG. 11 is a top plan view of FIG. 10;  
 FIG. 12 is a partial top, left perspective view of a fourth embodiment of FIG. 1, the only difference being a generally flat top surface without holes;  
 FIG. 13 is a top plan view of FIG. 12;  
 FIG. 14 is a right side view of a fifth embodiment of FIG. 1, the only difference being a clip rotatably affixed to a rear surface of the clock, the left side view being a mirror image;  
 FIG. 15 is a rear elevational view of the embodiment of FIG. 14; and,  
 FIG. 16 is a top plan view of the embodiment of FIG. 14.






FIG. 1





FIG. 2

FIG. 3





FIG. 6




FIG. 4




FIG. 5




FIG. 7

FIG. 8





FIG. 9




FIG. 11




FIG. 13




FIG. 10




FIG. 12




FIG. 15




FIG. 14




FIG. 16