



US00D362196S

United States Patent [19]

[11] Patent Number: **Des. 362,196**

Angelo et al.

[45] Date of Patent: **** Sep. 12, 1995**

- [54] **ROD GUIDE GAUGE**
- [75] Inventors: **Larry Angelo, Conroe; Lindell Trout, The Woodlands, both of Tex.**
- [73] Assignee: **J. M. Huber Corporation, Tomball, Tex.**
- [**] Term: **14 Years**
- [21] Appl. No.: **29,566**
- [22] Filed: **Oct. 11, 1994**
- [52] U.S. Cl. **D10/64; D10/65**
- [58] Field of Search **D10/64, 65; 33/555.1, 33/555.2, 562, 563, 566**

[56] **References Cited**
U.S. PATENT DOCUMENTS

D. 22,531	6/1893	Ford	D10/64
D. 243,389	2/1977	Lyon	D10/64
D. 251,059	2/1979	Montell	D10/64
367,365	8/1887	Clifford	33/562
375,949	1/1888	Peterson	33/563
3,139,003	6/1964	Magor	33/563

Primary Examiner—Antoine Duval Davis
Attorney, Agent, or Firm—Browning, Bushman, Anderson & Brookhart


[57] **CLAIM**

The ornamental design for a rod guide gauge, as shown and described.

DESCRIPTION

FIG. 1 is a back view of a rod guide gauge according to the present invention;
 FIG. 2 is a front view of the rod guide gauge as shown in FIG. 1;
 FIG. 3 is a left end view of the rod guide gauge as shown in FIG. 2;
 FIG. 4 is a right end view of the rod guide gauge as shown in FIG. 2;

FIG. 5 is a top view of the rod guide gauge as shown in FIG. 2;
 FIG. 6 is a bottom view of the rod guide gauge as shown in FIG. 2;
 FIG. 7 is a back view of another embodiment of a rod guide gauge according to the invention;
 FIG. 8 is a front view of the rod guide gauge as shown in FIG. 7;
 FIG. 9 is a left end view of the rod guide gauge as shown in FIG. 8;
 FIG. 10 is a right end view of the rod guide gauge as shown in FIG. 8;
 FIG. 11 is a top view of the rod guide gauge as shown in FIG. 8;
 FIG. 12 is a bottom view of the rod guide gauge as shown in FIG. 8;
 FIG. 13 is a back view of another embodiment of a rod guide gauge according to the invention;
 FIG. 14 is a front view of the rod guide gauge as shown in FIG. 13;
 FIG. 15 is a left end view of the rod guide gauge as shown in FIG. 14;
 FIG. 16 is a right end view of the rod guide gauge as shown in FIG. 14;
 FIG. 17 is a top view of the rod guide gauge as shown in FIG. 14;
 FIG. 18 is a bottom view of the rod guide gauge as shown in FIG. 14;
 FIG. 19 is a back view of a rod guide gauge according to the present invention;
 FIG. 20 is a front view of the rod guide gauge as shown in FIG. 19;
 FIG. 21 is a top view of the rod guide gauge as shown in FIG. 20;
 FIG. 22 is a bottom view of the rod guide gauge as shown in FIG. 20;
 FIG. 23 is a left side view of the rod guide gauge as shown in FIG. 20; and,
 FIG. 24 is a right side view of the rod guide gauge as shown in FIG. 20.
 The broken line showing of a ring and rod guide gauges are for illustrative purposes only and forms no part of the claimed design.






FIG. 1



FIG. 3




FIG. 2



FIG. 4



FIG. 5



FIG. 6




FIG. 7



FIG. 9




FIG. 8



FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14



FIG. 15



FIG. 16



FIG. 17



FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24