



US00D362638S

United States Patent [19]

[11] Patent Number: **Des. 362,638**

Greer et al.

[45] Date of Patent: ****Sep. 26, 1995**

[54] RECEIVER FOR CABLE AND FAULT LOCATOR SYSTEM

5,055,793	10/1991	Mulcahey	324/326
5,097,211	3/1992	Schonstedt	324/326
5,132,622	7/1992	Valentino	324/326

[75] Inventors: **Mark D. Greer**, Lenexa, Kans.; **Steven P. Gautieri**, Kansas City; **Jan J. Stefaniak**, Raytown, both of Mo.; **Ronald B. Kemnitzer**, Leawood, Kans.

Primary Examiner—Antoine Duval Davis
Attorney, Agent, or Firm—Hovey, Williams, Timmons & Collins

[73] Assignee: **Rycom Instruments, Inc.**, Raytown, Mo.

[57] CLAIM

[**] Term: **14 Years**

The ornamental design for a receiver for cable and fault locator system, as shown and described.

[21] Appl. No.: **12,807**

DESCRIPTION

[22] Filed: **Sep. 13, 1993**

[52] U.S. Cl. **D10/65**

[58] Field of Search D10/78; 324/66, 324/326, 327, 328, 329, 527, 528, 529, 530, 531, 532, 533, 520; 379/6, 21-26, 147

FIG. 1 is a front left perspective view;
FIG. 2 is a front right perspective view;
FIG. 3 is a right rear perspective view;
FIG. 4 is a side elevational view;
FIG. 5 is a front elevational view;
FIG. 6 is a bottom front perspective view; and,
FIG. 7 is a top plan view.

[56] References Cited

U.S. PATENT DOCUMENTS

D. 345,117 3/1994 Pacetti et al. D10/78 X

1 Claim, 2 Drawing Sheets




Fig. 2.




Fig. 1.





Fig. 3.






Fig. 7.




Fig. 4.




Fig. 6.

Fig. 5.

