



US00D365791S

United States Patent [19]

Brown et al.

[11] Patent Number: Des. 365,791

[45] Date of Patent: **Jan. 2, 1996

[54] TIRE TREAD

357419 11/1930 United Kingdom .
2221877 2/1990 United Kingdom .

[75] Inventors: **Stephanie C. Brown**, Akron; **Donald W. Gilliam**, Uniontown, both of Ohio; **Andy N. Hoang**, Schaumburg, Ill.; **Michael A. Kolowski**, Mogadore; **Frederick W. Miller**, Akron; **Anthony J. Scarpitti**, Uniontown; **Keith C. Trares**, Akron, all of Ohio

OTHER PUBLICATIONS

Tire Business, Sep. 6, 1993, p. 38.

Primary Examiner—James M. Gandy
Attorney, Agent, or Firm—T. P. Lewandowski

[73] Assignee: **The Goodyear Tire & Rubber Company**, Akron, Ohio

[**] Term: 14 Years

[21] Appl. No.: 26,881

[22] Filed: Aug. 11, 1994

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 21,350, Apr. 14, 1994, abandoned.

[52] U.S. Cl. D12/146

[58] Field of Search D12/142, 143,
D12/146-151; 152/209 R, 209 A, 209 B,
209 D

[56] References Cited

U.S. PATENT DOCUMENTS

D. 324,840	3/1992	Maxwell et al.	D12/147
D. 325,012	3/1992	Covert et al.	D12/147
D. 325,014	3/1992	Galante et al.	D12/147
D. 326,075	5/1992	Covert et al.	D12/147
D. 329,032	9/1992	Maxwell et al.	D12/147
D. 329,627	9/1992	Attinello et al.	D12/151
D. 336,273	6/1993	Kohara et al.	D12/147
D. 344,704	3/1994	Himuro et al.	D12/147
D. 347,412	5/1994	Croyle	D12/147

FOREIGN PATENT DOCUMENTS

296605A	6/1987	European Pat. Off. .
819836	10/1937	France .
61-166708	7/1986	Japan .

[57] CLAIM


The ornamental design for a tire tread, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a tire tread;
FIG. 2 is a right perspective view thereof;
FIG. 3 is a left perspective view thereof;
FIG. 4 is a right side view thereof;
FIG. 5 is a left side view thereof;
FIG. 6 is an enlarged fragmentary front view thereof;
FIG. 7 is a front elevational view of an additional embodiment thereof;
FIG. 8 is a right perspective view of FIG. 7;
FIG. 9 is a left perspective view of FIG. 7;
FIG. 10 is an enlarged fragmentary front view of FIG. 7;
FIG. 11 is a front elevational view of a third embodiment thereof;
FIG. 12 is a right perspective view of FIG. 11;
FIG. 13 is a left perspective view of FIG. 11;
FIG. 14 is an enlarged fragmentary front view of FIG. 11;
FIG. 15 is a front elevational view of a fourth embodiment thereof;
FIG. 16 is a right perspective view of FIG. 15;
FIG. 17 is a left perspective view of FIG. 15; and,
FIG. 18 is an enlarged fragmentary front view of FIG. 15.
The tread pattern is understood to be repeated uniformly through out the circumference of all four embodiments of the tire tread.

The broken line showing of the tire sidewall in the drawings is for illustrative purposes only and forms no part of the claimed design.

1 Claim, 18 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6




FIG-7




FIG-8




FIG-9




FIG-10




FIG-11




FIG-12




FIG-13




FIG-14




FIG-15




FIG-16




FIG-17




FIG-18