



US00D366433S

United States Patent [19]

[11] **Patent Number:** **Des. 366,433**

Evans et al.

[45] **Date of Patent:** ****Jan. 23, 1996**

[54] **MULTIPLE FUNCTION CHASSIS
DYNAMOMETER**

[76] Inventors: **Philip F. Evans**, 447 King Rd., West
Chester, Pa. 19380; **C. Eugene
Hutcheson**, 57 W. 58th St.- Apt. 3G,
New York, N.Y. 10019

[**] Term: **14 Years**

[21] Appl. No.: **18,926**

[22] Filed: **Feb. 18, 1994**

[52] U.S. Cl. **D10/83**

[58] **Field of Search** D10/46, 86; 73/117,
73/117.1, 117.2, 117.3, 119 R, 123, 124,
125, 126, 127, 128, 132, 193, 862, 862.14,
862.15, 862.16, 862.17, 862.18, 862.28,
862.193, 862.68

[56] **References Cited**

U.S. PATENT DOCUMENTS

1,517,106	11/1924	Donovan .	
2,185,246	1/1940	Cunningham .	
3,020,753	2/1962	Maxwell .	
3,289,471	12/1966	Maxwell .	
3,465,578	9/1969	Douglas .	
3,554,022	11/1970	Geul .	
3,577,777	5/1971	Whelan .	
3,680,369	8/1972	Merrill	73/117
3,952,589	4/1976	Geul .	
3,955,410	5/1976	Wakabayashi .	
3,979,950	9/1976	Maxwell .	
3,982,428	9/1976	Wilson .	
4,044,609	8/1977	Asmus .	
4,050,299	9/1977	Maxwell .	

4,932,252	6/1990	Bovenlander et al. .	
5,036,700	8/1991	Knetsel .	
5,111,685	5/1992	Langer	73/117
5,154,077	10/1992	Fujimori .	
5,269,179	12/1993	Vattakatto et al.	73/117

Primary Examiner—Antoine Duval Davis
Attorney, Agent, or Firm—Dennis H. Lambert

[57] **CLAIM**

The ornamental design for a multiple function chassis dynamometer, as shown and described.

DESCRIPTION

FIG. 1 is a top perspective view of the multiple function chassis dynamometer according to the invention, looking from the end opposite the motors;
FIG. 2 is a top perspective view of the multiple function chassis dynamometer of the invention, looking from the end in which the motors are supported;
FIG. 3 is a top plan view thereof;
FIG. 4 is a right side view thereof in elevation;
FIG. 5 is a left side view thereof in elevation;
FIG. 6 is a left end view thereof in elevation;
FIG. 7 is a right end view thereof in elevation;
FIG. 8 is a top perspective view of a modified form of multiple function chassis dynamometer according to the invention, viewed from the end opposite that containing the motors;
FIG. 9 is a top plan view thereof;
FIG. 10 is a right end view thereof in elevation;
FIG. 11 is a left end view thereof in elevation;
FIG. 12 is a right side view thereof in elevation; and,
FIG. 13 is a left side view thereof in elevation.

1 Claim, 6 Drawing Sheets




FIG. 1





FIG. 2







FIG. 3

FIG. 4






FIG. 5




FIG. 7




FIG. 6




FIG. 8




FIG. 9




FIG. 10




FIG. 11

FIG. 12





FIG. 13