

US00D371953S

United States Patent [19]

Ford et al.

[11] Patent Number: Des. 371,953

[45] Date of Patent: **Jul. 23, 1996

[54] DRAW LATCH

[75] Inventors: James J. Ford, Niskayuna, N.Y.; Lynn B. Ziemer, Ridley Park; Edward A.

McCormack, Media, both of Pa.

[73] Assignee: Southco, Inc., Concordville, Pa.

[**] Term: 14 Years

[21] Appl. No.: 43,116

[22] Filed: Aug. 25, 1995

Related U.S. Application Data

[60] Division of Ser. No. 27,634, Aug. 25, 1994, Pat. No. Des. 367,218, which is a continuation-in-part of Ser. No. 19,345, Feb. 28, 1994, abandoned.

[52] U.S. Cl. D8/331

[56] References Cited

U.S. PATENT DOCUMENTS

| D. 333,775 D. 348,210 3,145,038 3,174,784 3,936,082 | 6/1994 8/1964 3/1965 | Krape Bonzer Swanson . Swanson . Swanson . | |
|---|----------------------------|--|--|
| | 9/1985 1/1990 | Schenk . Frame et al Langkamp, Jr Gromotka . | |

OTHER PUBLICATIONS

Southco Fasteners Handbook 40 (Southco, Inc., Pennsylvania, 1990) Draw Latches, pp. H1-H30.

Camloc Fasteners Master Catalog 57 (Rexnord, Inc., Wisconsin, 1987) pp. F4-F5, H6-H7, H-10, H-12, I-2.

Primary Examiner—Brian N. Vinson Attorney, Agent, or Firm—Paul & Paul

[57] CLAIM

The ornamental design for a draw latch, as shown and described.

DESCRIPTION

FIG. 1 is a top plan view of a draw latch showing our new design;

FIG. 2 is a left-side elevational view thereof, the right side being a mirror image of that shown;

FIG. 3 is a front elevational view thereof;

FIG. 4 is a rear elevational view thereof;

FIG. 5 is a top plan view thereof, with the latch shown in an open position;

FIG. 6 is a left-side elevational view thereof, with the latch shown in an open position;

FIG. 7 is a top plan view of a second embodiment thereof, shown in an open position, the only difference from the first embodiment residing in the inclusion of a spring member and support;

FIG. 8 is a left-side elevational view of a third embodiment thereof, the only difference from the first embodiment residing in the configuration of the anchor mount;

FIG. 9 is a left-side elevational view of a fourth embodiment thereof, the only difference from the second embodiment residing in the configuration of the anchor mount;

FIG. 10 is a top plan view of a fifth embodiment of a draw latch showing our new design;

FIG. 11 is a left-side elevational view thereof, the right side being a mirror of that shown;

FIG. 12 is a front elevational view thereof;

FIG. 13 is a rear elevational view thereof;

FIG. 14 is a top plan view thereof, with the latch shown in an open position;

FIG. 15 is a left-side elevational view thereof, with the latch shown in an open position;

FIG. 16 is a top plan view of a sixth embodiment thereof, shown in an open position, the only difference from that of the fifth embodiment residing in the inclusion of a spring member and support;

FIG. 17 is a left-side elevational view of a seventh embodiment thereof, the only difference form that of the fifth embodiment residing in the configurtion of the anchor mount; and,




FIG. 18 is a left-side elevational view of an eightth embodiment thereof, the only difference from the sixth embodiment residing in the configuration of the anchor mount.

The broken-line disclosure of a portion of a surface in some

views is for illustrative purposes only and forms no part of the claimed design.

1 Claim, 6 Drawing Sheets




Fig. 1




Fig. 2




Fig. 4




Fig. 3




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9





Fig. 10






Fig. 13




Fig. 12




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18