



US00D374060S

United States Patent [19]

[11] Patent Number: **Des. 374,060**

Asano et al.

[45] Date of Patent: ***** Sep. 24, 1996**

[54] **ROTOR FOR A SPINNING FISHING REEL**

[75] Inventors: **Shinichi Asano**, Musashino; **Yasuhiro Takigasaki**, Higashikurume, both of Japan

[73] Assignee: **Daiwa Seiko, Inc.**, Higashikurume, Japan

[*] Notice: The portion of the term of this patent subsequent to Apr. 11, 2009, has been disclaimed.

[**] Term: **14 Years**

[21] Appl. No.: **18,891**

[22] Filed: **Feb. 17, 1994**

[30] **Foreign Application Priority Data**

Aug. 17, 1993 [JP] Japan 5-24996
Oct. 29, 1993 [JP] Japan 5-32954

[52] U.S. Cl. **D22/141**

[58] Field of Search D22/141; 242/230-233,
242/311

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 333,504 2/1993 Myojo D22/141
D. 352,763 11/1996 Myojo et al. D22/141
D. 355,014 1/1995 Furomoto D22/141

Primary Examiner—Doris V. Coles

Attorney, Agent, or Firm—Cushman Darby & Cushman, L.L.P.

[57] **CLAIM**

The ornamental design for a rotor for a spinning fishing reel, as shown and described.

DESCRIPTION

FIG. 1 is a front, bottom and right side of the perspective view of a rotor for a spinning fishing reel showing our new design;

FIG. 2 is a rear, top and left side of the perspective view thereof;

FIG. 3 is a front elevational view thereof;

FIG. 4 is a right side elevational view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a left side elevational view thereof;

FIG. 7 is a rear elevational view thereof;

FIG. 8 is a bottom view thereof;

FIG. 9 is a front, bottom and right side of the perspective view of another embodiment showing our new design;

FIG. 10 is a rear, top and left side of the perspective view thereof;

FIG. 11 is a front elevational view thereof;

FIG. 12 is a right side elevational view thereof;

FIG. 13 is a top plan view thereof;

FIG. 14 is a left side elevational view thereof;

FIG. 15 is a rear elevational view thereof; and,

FIG. 16 is a bottom view thereof.

1 Claim, 6 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15





FIG. 16



UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : D374,060

DATED : September 24, 1996

INVENTOR(S) : Shinichi Asano, et al

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page, [*] Notice: The portion of the term of this patent subsequent to Feb. 17, 2008, has been disclaimed.

Signed and Sealed this

Twenty-third Day of March, 1999

Attest:



Q. TODD DICKINSON

Attesting Officer

Acting Commissioner of Patents and Trademarks