



US00D374637S

# United States Patent [19]

[11] Patent Number: **Des. 374,637**

Esser

[45] Date of Patent: **\*\*Oct. 15, 1996**

[54] **EARRING**

[76] Inventor: **Margit Esser**, 10 Elm St., Peterborough, N.H. 03458

[\*\*] Term: **14 Years**

[21] Appl. No.: **16,905**

[22] Filed: **Dec. 29, 1993**

[52] U.S. Cl. .... **D11/44**

[58] Field of Search ..... 63/1.1, 2, 13; D11/40-54

### [56] **References Cited**

#### U.S. PATENT DOCUMENTS

|            |        |           |       |        |
|------------|--------|-----------|-------|--------|
| D. 334,003 | 3/1993 | Vogelsang | ..... | D11/44 |
| 3,071,938  | 1/1963 | Davidson  | ..... | 63/13  |

#### OTHER PUBLICATIONS

Tiffany & Co. Spring Selections 1989 Catalog, pp. 22-23 (Keyrings designated F and M).

*Primary Examiner*—Ralf Seifert

*Attorney, Agent, or Firm*—Hamilton, Brook, Smith & Reynolds, P.C.

### [57] **CLAIM**

The ornamental design for an earring, as shown and described.


### **DESCRIPTION**

FIG. 1 is a perspective view of an earring showing my new design, the broken line showing of an ear is for illustrative purposes only and forms no part of the claimed design; FIG. 2 is an exploded side elevational view; FIG. 3 is a rear elevational view;

FIG. 4 is a front elevational view; FIG. 5 is a top plan view; FIG. 6 is a bottom plan view; FIG. 7 is an earring showing a second embodiment of my new design, the wire being removed for ease of illustration; FIG. 8 is an earring showing a third embodiment of my new design, the wire being removed for ease of illustration; FIG. 9 is an earring showing a fourth embodiment of my new design, the wire being removed for ease of illustration; FIG. 10 is an earring showing a second embodiment of my new design, the wire being removed for ease of illustration; FIG. 11 is a top plan view of FIG. 7; FIG. 12 is a bottom plan view of FIG. 7; FIG. 13 is a front elevational view of FIG. 7; FIG. 14 is a rear elevational view of FIG. 7; FIG. 15 is a top plan view of FIG. 8; FIG. 16 is a bottom plan view of FIG. 8; FIG. 17 is a right side elevational view the opposite side being a mirror image; FIG. 18 is a top plan view of FIG. 9; FIG. 19 is a bottom plan view of FIG. 9; FIG. 20 is a right side elevational view of FIG. 9, the opposite side being a mirror image; FIG. 21 is a top plan view of FIG. 10; FIG. 22 is a bottom plan view of FIG. 10; FIG. 23 is an exploded view of the second embodiment, shown in its entirety; FIG. 24 is an exploded view of the fourth embodiment, shown in its entirety; FIG. 25 is an exploded view of the third embodiment, shown in its entirety; and, FIG. 26 is an exploded view of the fifth embodiment, shown in its entirety.

The wire attachment element, shown throughout the drawings, is rigid and is intended to be in the position shown.

**1 Claim, 4 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG 4




FIG. 7




FIG. 5



FIG. 8




FIG. 6




FIG. 9




FIG. 10



FIG. 11



FIG. 13



FIG. 12



FIG. 14



FIG. 18




FIG. 20



FIG. 19



FIG. 15



FIG. 16



FIG. 17




FIG. 21




FIG. 22

FIG. 24




FIG. 23




FIG. 26




FIG. 25

