



US00D374637S

# United States Patent [19]

[11] Patent Number: **Des. 374,637**

Esser

[45] Date of Patent: **\*\*Oct. 15, 1996**

[54] **EARRING**

[76] Inventor: **Margit Esser**, 10 Elm St., Peterborough, N.H. 03458

[\*\*] Term: **14 Years**

[21] Appl. No.: **16,905**

[22] Filed: **Dec. 29, 1993**

[52] U.S. Cl. .... **D11/44**

[58] Field of Search ..... 63/1.1, 2, 13; D11/40-54

### [56] **References Cited**

#### U.S. PATENT DOCUMENTS

D. 334,003	3/1993	Vogelsang	.....	D11/44
3,071,938	1/1963	Davidson	.....	63/13

#### OTHER PUBLICATIONS

Tiffany & Co. Spring Selections 1989 Catalog, pp. 22-23 (Keyrings designated F and M).

*Primary Examiner*—Ralf Seifert

*Attorney, Agent, or Firm*—Hamilton, Brook, Smith & Reynolds, P.C.

### [57] **CLAIM**


The ornamental design for an earring, as shown and described.

### **DESCRIPTION**

FIG. 1 is a perspective view of an earring showing my new design, the broken line showing of an ear is for illustrative purposes only and forms no part of the claimed design;  
 FIG. 2 is an exploded side elevational view;  
 FIG. 3 is a rear elevational view;

FIG. 4 is a front elevational view;  
 FIG. 5 is a top plan view;  
 FIG. 6 is a bottom plan view;  
 FIG. 7 is an earring showing a second embodiment of my new design, the wire being removed for ease of illustration;  
 FIG. 8 is an earring showing a third embodiment of my new design, the wire being removed for ease of illustration;  
 FIG. 9 is an earring showing a fourth embodiment of my new design, the wire being removed for ease of illustration;  
 FIG. 10 is an earring showing a second embodiment of my new design, the wire being removed for ease of illustration;  
 FIG. 11 is a top plan view of FIG. 7;  
 FIG. 12 is a bottom plan view of FIG. 7;  
 FIG. 13 is a front elevational view of FIG. 7;  
 FIG. 14 is a rear elevational view of FIG. 7;  
 FIG. 15 is a top plan view of FIG. 8;  
 FIG. 16 is a bottom plan view of FIG. 8;  
 FIG. 17 is a right side elevational view the opposite side being a mirror image;  
 FIG. 18 is a top plan view of FIG. 9;  
 FIG. 19 is a bottom plan view of FIG. 9;  
 FIG. 20 is a right side elevational view of FIG. 9, the opposite side being a mirror image;  
 FIG. 21 is a top plan view of FIG. 10;  
 FIG. 22 is a bottom plan view of FIG. 10;  
 FIG. 23 is an exploded view of the second embodiment, shown in its entirety;  
 FIG. 24 is an exploded view of the fourth embodiment, shown in its entirety;  
 FIG. 25 is an exploded view of the third embodiment, shown in its entirety; and,  
 FIG. 26 is an exploded view of the fifth embodiment, shown in its entirety.  
 The wire attachment element, shown throughout the drawings, is rigid and is intended to be in the position shown.

**1 Claim, 4 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 7




FIG. 5



FIG. 8




FIG. 6




FIG. 9




FIG. 10



FIG. 11



FIG. 13



FIG. 12



FIG. 14



FIG. 18



FIG. 20



FIG. 19



FIG. 15



FIG. 16



FIG. 17




FIG. 21




FIG. 22



FIG. 24




FIG. 23




FIG. 26




FIG. 25

