



US00D375717S

United States Patent [19] Dick

[11] Patent Number: **Des. 375,717**
[45] Date of Patent: ****Nov. 19, 1996**

[54] ANCHOR

[76] Inventor: **Ian G. Dick**, P.O. Box 290, Whangarei, New Zealand

[**] Term: **14 Years**

[21] Appl. No.: **34,805**

[22] Filed: **Feb. 10, 1995**

[30] Foreign Application Priority Data

Aug. 10, 1994 [NZ] New Zealand 26089

[52] U.S. Cl. **D12/215**

[58] Field of Search D12/215; 114/301, 114/303, 304

[56] References Cited

U.S. PATENT DOCUMENTS

1,974,933	9/1934	Taylor	114/304
2,507,563	5/1950	Farren	114/304
2,948,249	8/1960	Gesner et al.	114/303
4,781,142	11/1988	Cheung	114/304
4,827,863	5/1989	Scholz et al.	114/301
5,138,967	8/1992	McCarron et al.	114/301
5,154,133	10/1992	Hallerberg	114/303

FOREIGN PATENT DOCUMENTS

72260 3/1934 New Zealand .

180787	10/1979	New Zealand .
226075	9/1988	New Zealand .
228656	4/1989	New Zealand .
237058	2/1991	New Zealand .

Primary Examiner—Kay H. Chin
Attorney, Agent, or Firm—Brooks & Kushman P.C.

[57] CLAIM

The ornamental design for an anchor, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the anchor with its fluke maintained in an operative condition by a shear pin;

FIG. 2 is a view similar to FIG. 1 except that the shear pin is shown severed and the fluke is shown in a released condition;


FIG. 3 is a front elevational view of the anchor shown in FIG. 1;

FIG. 4 is a perspective view of part of the anchor showing the fluke in an operative condition;

FIG. 5 is a perspective view of part of the anchor showing the fluke in a released condition;

FIG. 6 is a bottom view of the anchor shown in FIG. 2; and, FIG. 7 is a rear view of the anchor shown in FIG. 2.

1 Claim, 5 Drawing Sheets






Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7