



US00D377597S

United States Patent [19]

[11] Patent Number: **Des. 377,597**

Podgers

[45] Date of Patent: ****Jan. 28, 1997**

[54] **WISE JAW**

[75] Inventor: **Alexander R. Podgers**, Lake City, Pa.

[73] Assignee: **Reed Manufacturing Company**, Erie, Pa.

[**] Term: **14 Years**

[21] Appl. No.: **34,986**

[22] Filed: **Dec. 30, 1994**

[52] U.S. Cl. **D8/349**; D8/74

[58] Field of Search D8/74, 354, 380, D8/374, 349; D6/400; 29/560.1; 269/130, 241, 243, 279; D15/140

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 299,112	12/1988	Downey	D8/354
D. 315,863	4/1991	Shui-Mu	D8/354
D. 345,265	3/1994	McIntyre	D6/400
1,158,414	10/1915	Amborn .	
1,184,388	5/1916	Schubert .	
1,807,917	6/1931	Jones	269/130
2,455,517	12/1948	Nielson	269/130
2,648,242	8/1953	Walter	269/130
2,703,027	3/1955	Petersen	269/130
2,968,978	1/1961	Wheeler	269/130
4,454,901	6/1984	Thorsness	D15/133

OTHER PUBLICATIONS

Ridgid No. 450 Tristand Chain Vise The Ridge Tool Company, Elyria, Ohio, date unknown.

BT-333 Tristand Chain Vise The Berkley Tool, Jupiter, Florida, date unknown.

Reed Chain Vise advertisement, *Industrial Equipment News*, Oct. 1962, p. 92.

Primary Examiner—James Gandy
Assistant Examiner—Robert M. Spear
Attorney, Agent, or Firm—Howson and Howson

[57] **CLAIM**

The ornamental design for a vise jaw, as shown and described.

DESCRIPTION

FIG. 1 is a front plan view of a vise jaw according to the present invention, the rear surface of the vise jaw being a mirror image thereof;

FIG. 2 is a right side elevational view of FIG. 1 illustrating the teeth of the present invention, the left side being a mirror image thereof;

FIG. 3 is a bottom side elevational view of FIG. 1, the top being a mirror image thereof;

FIG. 4 is a plan view of an alternate embodiment of a vise jaw according to the present invention;

FIG. 5 is a rear plan view of the vise jaw of FIG. 4;

FIG. 6 is a left side elevational view of FIG. 4 illustrating the teeth of the vise jaw;

FIG. 7 is a right side elevational view of FIG. 4 illustrating the rubber friction pad of the vise jaw;

FIG. 8 is a top end view of FIG. 4, the bottom end view being a mirror image thereof;

FIG. 9 is a plan view of a second alternate embodiment of a vise jaw according to the present invention, the rear surface of the vise jaw being a mirror image thereof;

FIG. 10 is a right side elevational view of FIG. 9 illustrating the teeth of the vise jaw, the left side being a mirror image thereof; and,

FIG. 11 is a top end view of FIG. 9, the bottom being a mirror image thereof.

1 Claim, 3 Drawing Sheets




FIG. 1




FIG. 2



FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

