



US00D379787S

United States Patent [19]

Maxwell et al.

[11] Patent Number: **Des. 379,787**

[45] Date of Patent: ****Jun. 10, 1997**

[54] **TIRE TREAD**

[75] Inventors: **Paul B. Maxwell, Mamer; Maurice Graas, Reichlange; John C. M. Munster, Bridel, all of Luxembourg**

[73] Assignee: **The Goodyear Tire & Rubber Company, Akron, Ohio**

[**] Term: **14 Years**

[21] Appl. No.: **41,886**

[22] Filed: **Jul. 26, 1995**

[51] LOC (6) Cl. **12-15**

[52] U.S. Cl. **D12/147**

[58] Field of Search D12/136, 141, D12/146-151; 152/209 R, 209 D

[56] References Cited

U.S. PATENT DOCUMENTS

| | | | |
|------------|---------|-----------------------|---------|
| D. 288,915 | 3/1987 | Kadomaru | D12/147 |
| D. 292,079 | 9/1987 | Ikeda | D12/145 |
| D. 294,931 | 3/1988 | Ikeda | D12/147 |
| D. 294,932 | 3/1988 | Hayama | D12/147 |
| D. 296,682 | 7/1988 | Turchetti et al. | D12/147 |
| D. 336,273 | 6/1993 | Kohara et al. | D12/147 |
| D. 336,627 | 6/1993 | Hirose | D12/147 |
| D. 337,291 | 7/1993 | Hirose | D12/147 |
| D. 340,895 | 11/1993 | Himuro | D12/147 |
| D. 341,112 | 11/1993 | Kobayashi et al. | D12/147 |
| D. 341,347 | 11/1993 | Kobayashi | D12/147 |
| D. 344,054 | 2/1994 | Attinello et al. | D12/151 |
| D. 350,103 | 8/1994 | Graas | D12/151 |
| D. 355,876 | 2/1995 | Diensthuber | D12/151 |

| | | | |
|------------|---------|----------------------|-----------|
| D. 358,793 | 5/1995 | Himuro et al. | D12/151 |
| 4,726,407 | 6/1981 | Hayakawa | 152/209 R |
| 5,154,783 | 10/1992 | Kuhr et al. | 152/209 R |
| 5,178,697 | 1/1993 | Watanabe et al. | 152/209 R |
| 5,223,059 | 6/1993 | Himuro | 152/209 R |
| 5,234,042 | 8/1993 | Kuhr et al. | 152/209 R |
| 5,370,168 | 12/1994 | Boiocchi et al. | 152/209 R |
| 5,375,639 | 12/1994 | Suzuki et al. | 152/209 R |
| 5,423,364 | 6/1995 | Himuro | 152/209 R |

OTHER PUBLICATIONS

Toyo Proxes Z1 tire, *1994 Tread Design Guide*, p. 63.

Primary Examiner—James M. Gandy
Assistant Examiner—Robert M. Spear
Attorney, Agent, or Firm—T. P. Lewandowski


[57] CLAIM

The ornamental design for a tire tread, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire tread, it being understood that the pattern is repeated uniformly throughout the circumference of the tread;
FIG. 2 is a front elevational view thereof;
FIG. 3 is a side elevational view thereof;
FIG. 4 is an opposite side elevational view thereof; and,
FIG. 5 is an enlarged fragmentary front view thereof.
In the drawings, the broken lines defining the inner bead of the sidewall and the peripheral boundary between the tire tread and the sidewall are for illustrative purposes only and form no part of the claimed design.

1 Claim, 5 Drawing Sheets






FIG-1



FIG-2




FIG-3




FIG-4




FIG-5