

US00D381607S

United States Patent [19]
Attinello et al.

[11] **Patent Number:** **Des. 381,607**
[45] **Date of Patent:** ****Jul. 29, 1997**

[54] **TIRE TREAD**

[75] **Inventors:** **John Steven Attinello**, Hartville, Ohio;
Kevin Alan Reid, Asheville, N.C.

[73] **Assignee:** **The Goodyear Tire & Rubber Company**, Akron, Ohio

[**] **Term:** **14 Years**

[21] **Appl. No.:** **53,262**

[22] **Filed:** **Apr. 17, 1996**

[51] **LOC (6) Cl.** **12-15**

[52] **U.S. Cl.** **D12/147**

[58] **Field of Search** D12/141, 142,
D12/143, 146, 147, 148; 152/209 R, 209 D

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 272,815	2/1984	Hatakenaka		D12/146
D. 283,501	4/1986	Hitzky		D12/147
D. 284,178	6/1986	Kawabata et al.		D12/147
D. 284,562	7/1986	Kojima et al.		D12/147
D. 287,840	1/1987	Ono		D12/147
D. 292,080	9/1987	Hayakawa et al.		D12/146
D. 301,024	5/1989	Himuro et al.		D12/147
D. 301,855	6/1989	Ono		D12/147
D. 307,407	4/1990	Minamitani		D12/147
D. 313,781	1/1991	Kuroda		D12/147
D. 316,534	4/1991	Hutz		D12/147
D. 317,145	5/1991	Iwamura		D12/146
D. 320,969	10/1991	Kobayashi et al.		D12/147
D. 324,665	3/1992	Davis et al.		D12/146
D. 329,031	9/1992	Lassan		D12/146
D. 335,844	5/1993	Boiocchi et al.		D12/147
D. 339,558	9/1993	Sulkowski		D12/146
D. 347,607	6/1994	Montag et al.		D12/147
D. 348,862	7/1994	Daisho et al.		D12/147
D. 349,675	8/1994	Shinohara et al.		D12/147
D. 350,509	9/1994	Killian		D12/146
D. 350,930	9/1994	Sugimoto		D12/147
D. 354,725	1/1995	McKisson		D12/146
D. 356,059	3/1995	McKisson		D12/146
4,649,975	3/1987	Kogure et al.		152/209

4,773,459	9/1988	Yamaoka et al.		152/209
4,945,963	8/1990	Fujiwara		152/209
5,027,875	7/1991	Kogure		152/209
5,109,903	5/1992	Watanabe et al.		152/209
5,147,478	9/1992	Nock et al.		152/209
5,152,852	10/1992	Hisamichi et al.		152/209
5,343,914	9/1994	Wako		152/209

OTHER PUBLICATIONS

Mohawk SR-1000 Metric tire, *1994 Tread Design Guide*, p. 43, bottom row, second from right.

Pos-A-Traction Twister tire, *1994 Tread Design Guide*, p. 51, bottom row, far right.

Star Hydroguard tire, *1994 Tread Design Guide*, p. 58, bottom row, far right.

Cooper Lifeliner Classic II tire, *1995 Tread Design Guide*, p. 17, second row, center.

Hercules Ultra AQT tire, *1995 Tread Design Guide*, p. 35, third row, second from left.

Sears Goodyear Weatherhandler tire, *1995 Tread Design Guide*, p. 61, top row, far right.

Primary Examiner—James Gandy

Assistant Examiner—Robert M. Spear

Attorney, Agent, or Firm—T. P. Lewandowski

[57] **CLAIM**

The ornamental design for a tire tread, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire tread, it being understood that the tread pattern repeats uniformly throughout the circumference of the tread;


FIG. 2 is a front elevational view thereof;

FIG. 3 is a side elevational view thereof the opposite side elevational view being identical thereto; and,

FIG. 4 is an enlarged fragmentary front view thereof.

The broken line showing of the tire sidewall in the drawings is for illustrative purposes only and forms no part of the claimed design.

1 Claim, 4 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4