



US00D381629S

# United States Patent [19]

Goto

[11] Patent Number: Des. 381,629

[45] Date of Patent: \*\*Jul. 29, 1997

## [54] CABLE CONNECTOR ASSEMBLY

[75] Inventor: Teiyu Goto, Tokyo, Japan

[73] Assignee: Sony Corporation, Tokyo, Japan

[\*\*] Term: 14 Years

[21] Appl. No.: 45,896

[22] Filed: Nov. 1, 1995

### [30] Foreign Application Priority Data

May 9, 1995 [JP] Japan ..... 7-12724

[51] LOC (6) Cl. .... 13-03

[52] U.S. Cl. .... D13/147

[58] Field of Search ..... D13/146, 147;  
439/502, 607, 620; 333/185

### [56] References Cited

#### U.S. PATENT DOCUMENTS

D. 314,186 1/1991 Fujioka ..... D13/199

D. 363,700 10/1995 Buongervino et al. .... D13/147

4,508,414 4/1985 Kusui et al. .... 339/143 R

#### OTHER PUBLICATIONS

Molex Duplex fiber optic connector on p. 9H of Molex catalog No. 980. Mar. 1991.

Primary Examiner—Joel Sincavage

Attorney, Agent, or Firm—Foley & Lardner

### [57] CLAIM

The ornamental design for a cable connector assembly, as shown and described.

### DESCRIPTION

FIG. 1 is a perspective view of a first embodiment of the cable connector assembly including my new design;

FIG. 2 is a top plan view thereof;

FIG. 3 is a left side elevational view thereof;

FIG. 4 is a front elevational view thereof;

FIG. 5 is a bottom plan view thereof;

FIG. 6 is a right side elevational view thereof;

FIG. 7 is a rear elevational view thereof;

FIG. 8 is a front perspective view of a second embodiment of the cable connector assembly including my new design;

FIG. 9 is a rear perspective view of a second embodiment of FIG. 8;

FIG. 10 is a top plan view of the embodiment of FIG. 8;

FIG. 11 is a left side elevational view of the embodiment of FIG. 8;

FIG. 12 is a front elevational view of the embodiment of FIG. 8;

FIG. 13 is a bottom plan view of the embodiment of FIG. 8;

FIG. 14 is a rear elevational view of the embodiment of FIG. 8;

FIG. 15 is a right side elevational view of the embodiment of FIG. 8;

FIG. 16 is a front perspective view of a third embodiment of the cable connector assembly including my new design;

FIG. 17 is a rear perspective view of the embodiment of FIG. 16;

FIG. 18 is a top plan view of the embodiment of FIG. 16;

FIG. 19 is a left side elevational view of the embodiment of FIG. 16;

FIG. 20 is a front elevational view of the embodiment of FIG. 16;


FIG. 21 is a bottom plan view of the embodiment of FIG. 16;

FIG. 22 is a rear elevational view of the embodiment of FIG. 16; and,

FIG. 23 is a right side elevational view of the embodiment of FIG. 16.

The cord is shown broken away in FIGS. 1, 2, 4, 5 and 7 to indicate indeterminate length.

1 Claim, 5 Drawing Sheets






FIG. 1

FIG. 2




FIG. 4




FIG. 3



FIG. 5




FIG. 6



FIG. 7




FIG. 8




FIG. 9




FIG. 10



FIG. 11



FIG. 12



FIG. 14



FIG. 15



FIG. 13








FIG. 18




FIG. 16




FIG. 17

FIG. 19



FIG. 20



FIG. 22




FIG. 23



FIG. 21

