



US00D385010S

United States Patent [19]

[11] Patent Number: Des. 385,010

Hennessy

[45] Date of Patent: **Oct. 14, 1997

[54] SPRAY NOZZLE BODY

[75] Inventor: Timothy H. Hennessy, Aurora, Ill.

[73] Assignee: Spraying Systems Co., Wheaton, Ill.

[**] Term: 14 Years

[21] Appl. No.: 43,501

[22] Filed: Sep. 5, 1995

[51] LOC (6) Cl. 23-01

[52] U.S. Cl. D23/213

[58] Field of Search D23/213, 223-230;
239/394, 373, 600

[56] References Cited

U.S. PATENT DOCUMENTS

D. 134,562	12/1942	Murphy	D23/213
D. 198,356	6/1964	Wahlin	D23/213
D. 218,824	9/1970	Lawrence et al.	D23/213
D. 345,545	3/1994	Haruch	D23/213
4,438,884	3/1984	O'Brien et al.	239/600
4,527,745	7/1985	Butterfield et al.	239/600
5,190,224	3/1993	Hamilton	239/600
5,333,794	8/1994	Haruch	239/600

OTHER PUBLICATIONS

Catalog 70, TeeJet® Spray Products, catalog, front and back cover and pp. 25-29.

Drawings for copending U.S. application No. 08/397,914.

Drawings for copending U.S. application No. 08/523,227.

Primary Examiner—Joel Sincavage

Assistant Examiner—Robin V. Taylor

Attorney, Agent, or Firm—Leydig, Voit & Mayer, Ltd.

[57] CLAIM

The ornamental design for a spray nozzle body, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a spray nozzle body showing my new design, the broken line showing of a spray

tip is for illustrative purposes only and forms no part of the claimed design;

FIG. 2 is a rear perspective view of the spray nozzle body as in FIG. 1 embodying the design of the present invention;

FIG. 3 is a left side elevational view thereof, the right side elevational view thereof being a mirror image;

FIG. 4 is a top plan view thereof;

FIG. 5 is a bottom plan view thereof;

FIG. 6 is a rear elevational view thereof;

FIG. 7 is a front elevational view thereof;

FIG. 8 is a front perspective view of a spray nozzle body in another embodiment of the design of the present invention, showing spray tip locking detents in slightly circumferentially offset relation to that shown in the embodiment of FIGS. 1-7;

FIG. 9 is a top plan view of the embodiment of FIG. 8, the other views thereof being identical with the corresponding views of the embodiment of FIG. 1;

FIG. 10 is a front perspective view of another embodiment thereof, the broken line showing of a spray tip is for illustrative purposes only and forms no part of the claimed design;

FIG. 11 is a rear perspective view of the spray nozzle body as in FIG. 10 embodying the design of the present invention; FIG. 12 is a left side elevational view of the embodiment of FIG. 10, the right side elevational view thereof being a mirror image;



FIG. 13 is a top plan view of the embodiment of FIG. 10; FIG. 14 is a bottom plan view of the embodiment of FIG. 10; FIG. 15 is a rear elevational view of the embodiment of FIG. 10;

FIG. 16 is a front elevational view of the embodiment of FIG. 10;

FIG. 17 is a front perspective view of a spray nozzle body in another embodiment of the design of the present invention with spray tip locking detents in slight circumferentially offset relation from that shown in the embodiment of FIGS. 10-16; and,

FIG. 18 is a top plan view of the embodiment of FIG. 17, the other views thereof being identical with the corresponding views of the embodiment of FIG. 10.

1 Claim, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18