

# United States Patent [19]

### Mercer et al.

[11] Patent Number: Des. 385,209

[45] Date of Patent: \*\*Oct. 21, 1997

# [54] COMBINED TRANSMITTER AND RECEIVER FOR A FAILURE DETECTOR UNIT

[75] Inventors: Jeffrey L. Mercer, Hendersonville;

Jerrell J. Duckworth, Chattanooga,

both of Tenn.

[73] Assignee: GoPro Inc., Hendersonville, Tenn.

[\*\*] Term: 14 Years

[21] Appl. No.: 53,696

[22] Filed: Apr. 26, 1996

[52] U.S. Cl. ...... D10/106

D10/116, 121; 340/371, 372, 373, 571, 572, 573, 628, 629, 630

[56] References Cited

U.S. PATENT DOCUMENTS

Primary Examiner—Marcus A. Jackson
Attorney, Agent, or Firm—Waddey & Patterson; Laura
Thomas

[57] CLAIM

The ornamental design for a combined transmitter and receiver for a failure detector unit, as shown and described.

#### **DESCRIPTION**

FIG. 1 is a front elevation of the combined transmitter and

receiver for a failure detector unit of the present invention. The transmitter is shown on the right side and the receiver is shown on the left side;

FIG. 2 is a left side elevation of the receiver of the present invention;

FIG. 3 is a right side elevation of the receiver of the present invention;

FIG. 4 is a back elevation of the receiver of the present invention;

FIG. 5 is a top view of the receiver of the present invention;

FIG. 6 is a bottom view of the receiver of the present invention;

FIG. 7 is a left side elevation of the transmitter of the present invention;


FIG. 8 is a right side elevation of the transmitter of the present invention;


FIG. 9 is a back elevation of the transmitter of the present invention;


FIG. 10 is a top view of the transmitter of the present invention; and,


FIG. 11 is a bottom view of the transmitter of the present invention.


## 1 Claim, 3 Drawing Sheets











Oct. 21, 1997

