



US00D386110S

United States Patent [19]

[11] **Patent Number: Des. 386,110**

Hetrick et al.

[45] **Date of Patent: **Nov. 11, 1997**

[54] **STRAP ADJUSTER**

[75] **Inventors: Westly D. Hetrick; Yasutaka Nishida,**
both of Macon, Ga.

[73] **Assignee: YKK Corporation of America,**
Marietta, Ga.

[**] **Term: 14 Years**

[21] **Appl. No.: 59,871**

[22] **Filed: Sep. 17, 1996**

[51] **LOC (6) Cl. 02-07**

[52] **U.S. Cl. D11/218**

[58] **Field of Search D11/200, 201,**
D11/215-218, 231, 234; 24/196, 616, 625,
650, 200, 171

| | | |
|-----------|--------|-----------------|
| 4,903,378 | 2/1990 | Kasai . |
| 5,123,153 | 6/1992 | Krauss . |
| 5,216,786 | 6/1993 | Anscher . |
| 5,243,741 | 9/1993 | Fudaki et al. . |
| 5,307,542 | 5/1994 | Murai . |
| 5,331,726 | 7/1994 | Suh . |

FOREIGN PATENT DOCUMENTS

| | | |
|--------|---------|---------|
| 665284 | 8/1985 | Japan . |
| 665305 | 8/1985 | Japan . |
| 690910 | 7/1986 | Japan . |
| 748416 | 7/1988 | Japan . |
| 764052 | 3/1989 | Japan . |
| 863378 | 12/1992 | Japan . |
| 922922 | 1/1995 | Japan . |
| 941664 | 9/1995 | Japan . |
| 945120 | 11/1995 | Japan . |

Primary Examiner—Ralf Seifert
Attorney, Agent, or Firm—Hill, Steadman & Simpson

[56] **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|------------|---------|-----------------|---------|
| D. 328,044 | 7/1992 | Murai . | |
| D. 328,045 | 7/1992 | Matoba | D11/218 |
| D. 340,008 | 10/1993 | Anscher | D11/218 |
| D. 347,601 | 6/1994 | Anscher | D11/218 |
| D. 349,665 | 8/1994 | Franklin . | |
| D. 352,254 | 11/1994 | Prosser | D17/200 |
| D. 356,491 | 3/1995 | Anscher . | |
| D. 359,710 | 6/1995 | Chinni et al. . | |
| D. 364,833 | 12/1995 | Matoba . | |
| 4,171,555 | 10/1979 | Bakker et al. . | |
| 4,571,783 | 2/1986 | Kasai . | |
| 4,608,735 | 9/1986 | Kasai . | |
| 4,637,099 | 1/1987 | Kasai . | |
| 4,677,711 | 7/1987 | Anscher | 24/200 |
| 4,791,709 | 12/1988 | Fildan | 24/171 |
| 4,843,689 | 7/1989 | Fildan . | |

[57] **CLAIM**

The ornamental design for a strap adjuster, as shown and described.

DESCRIPTION

FIG. 1 is a front view of a strap adjuster showing my new design;
FIG. 2 is a back view of the strap adjuster of FIG. 1;
FIG. 3 is a top view of the strap adjuster of FIG. 1;
FIG. 4 is a bottom view of the strap adjuster of FIG. 1;
FIG. 5 is a right side view of the strap adjuster of FIG. 1;
FIG. 6 is a left side view of the strap adjuster of FIG. 1; and,
FIG. 7 is a sectional view taken generally along line VII—VII of FIG. 1.

1 Claim, 3 Drawing Sheets




FIG. 1




FIG. 2




FIG. 6




FIG. 5




FIG. 3




FIG. 4




FIG. 7

