US00D386157S

United States Patent [19]

Hasegawa

[11] **Patent Number: Des. 386,157**

[45] **Date of Patent: **Nov. 11, 1997**

[54] **IMAGE SCANNER**

[75] Inventor: **Fumio Hasegawa**, Nishio, Japan

[73] Assignee: **Elmo Company, Limited**, Japan

[**] Term: **14 Years**

[21] Appl. No.: **56,336**

[22] Filed: **Jun. 27, 1996**

[30] **Foreign Application Priority Data**

Dec. 28, 1995 [JP] Japan 7-39442
May 8, 1996 [JP] Japan 8-13360

[51] **LOC (6) Cl.** **14-02**
[52] **U.S. Cl.** **D14/107**; D16/202
[58] **Field of Search** D14/100, 107, D14/118; D18/36, 37, 39; D16/208, 202, 214, 223, 232; 250/556; 355/64, 65, 75; 235/454, 462, 470, 472, 476, 482, 483; 358/408, 472, 474, 497

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 305,228	12/1989	Allgeier	D14/107
D. 306,435	3/1990	Krichever et al.	D14/107
D. 364,388	11/1995	Miyahara	D14/107
D. 376,586	12/1996	Shinano	D14/107
4,825,295	4/1989	Ishikawa et al.	D14/107 X

OTHER PUBLICATIONS

Brochure entitled, "Video Visualizer Vizcam 1000" by Canon, Issue Date: May 1996.

Brochure entitled, "Scopeman Flex" by Moritex Corp. Issue Date: Sep. 1995.

Brochure entitled, "CCD–PC1M/CCD–PC–1" by Sony, Issue Date: Jul. 1995.

Broochure entitled, "VP–S" by Uchida, Issue Date: Mar. 195.

Primary Examiner—Freda Nunn
Attorney, Agent, or Firm—Ostrolenk, Faber, Gerb & Soffen, LLP

[57] **CLAIM**

The ornamental design for an image scanner, as shown and described.

DESCRIPTION

FIG. **1** is a front view of the first image scanner embodying my new design;

FIG. **2** is a rear view thereof;

FIG. **3** is a left side view thereof;

FIG. **4** is a right side view thereof;

FIG. **5** is a bottom side view thereof;

FIG. **6** is a top plan view thereof;

FIG. **7** is a perspective view as seen from the top and left front of present FIG. **1**;

FIG. **8** is a perspective view as seen from the top and right front of present FIG. **1**;

FIG. **9** is a perspective view as seen from the top and left front of the first image scanner in a usable position with a TV camera thereof facing to the left;

FIG. **10** is a perspective view as seen from the top and right front of the first image scanner in a usable position with the TV camera thereof facing to the left;

FIG. **11** is a front view of the first image scanner placed on the stand in such a manner that the TV camera lens thereof faces the front;

FIG. **12** is a rear view of the first image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **13** is a left side view of the first image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **14** is a right side view of the first image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **15** is a bottom side view of the first image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **16** is a top plan view of the first image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **17** is a perspective view as seen from the top and left front of the first image scanner placed on the stand in such a manner that the TV camera lens faces the front;



FIG. **18** is a perspective view as seen from the top and right front of the first image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **19** is a perspective view as seen from the top and left front of the first image scanner placed on the stand in such a manner that the TV camera lens faces to the left of the front;

FIG. **20** is a perspective view as seen from the top and right front of the first image scanner placed on the stand in such a manner that the TV camera lens faces to the left of the front;

FIG. **21** is a perspective view as seen from the top and left front of the first image scanner with the front-facing TV camera being slanted up and the stand in an upright position;

FIG. **22** is a perspective view as seen from the top and right front of the first image scanner with the front-facing TV camera being slanted up and the stand in an upright position;

FIG. **23** is a front view of the second image scanner embodying my new design;

FIG. **24** is a rear view thereof;

FIG. **25** is a left side view thereof;

FIG. **26** is a right side view thereof;

FIG. **27** is a bottom side view thereof;

FIG. **28** is a top plan view thereof;

FIG. **29** is a perspective view as seen from the top and left front of present FIG. **23**;

FIG. **30** is a perspective view as seen from the top and right front of present FIG. **23**;

FIG. **31** is a perspective view as seen from the top and left front of the second image scanner in a usable position with a TV camera thereof facing to the left;

FIG. **32** is a perspective view as seen from the top and right front of the second image scanner in a usable position with the TV camera thereof facing to the left;

FIG. **33** is front view of the second image scanner placed on the stand in such a manner that the TV camera lens thereof faces the front;

FIG. **34** is a rear view of the second image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **35** is a left side view of the second image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **36** is a right side view of the second image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **37** is a bottom side view of the second image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **38** is a top plan view of the second image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **39** is a perspective view as seen from the top and left front of the second image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **40** is a perspective view as seen from the top and right front of the second image scanner placed on the stand in such a manner that the TV camera lens faces the front;

FIG. **41** is perspective view as seen from the top and left front of the second image scanner placed on the stand in such a manner that the TV camera lens faces to the left of the front;

FIG. **42** is a perspective view as seen from the top and right front of the second image scanner placed on the stand in such a manner that the TV camera lens faces to the left of the front;

FIG. **43** is a perspective view as seen from the top and left front of the second image scanner with the front-facing TV camera being slanted up and the stand in an upright position; and,

FIG. **44** is perspective view as seen from the top and right front of the second image scanner with the front-facing TV camera being slanted up and the stand in an upright position.

1 Claim, 44 Drawing Sheets

Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9



Fig. 10



Fig. 11



Fig. 12



Fig. 13



Fig. 14



Fig. 15



Fig. 16



Fig. 17



Fig. 18



Fig. 19



Fig. 20



Fig. 21



Fig. 22



Fig. 23



Fig. 24



Fig. 25



Fig. 26



Fig. 27



Fig. 28



Fig. 29



Fig. 30



Fig. 31



Fig. 32



Fig. 33



Fig. 34



Fig. 35



Fig. 36



Fig. 37



Fig. 38



Fig. 39



Fig. 40



Fig. 41



Fig. 42



Fig. 43



Fig. 44