



US00D387971S

United States Patent [19] Nemeckay

[11] Patent Number: **Des. 387,971**
[45] Date of Patent: ****Dec. 23, 1997**

[54] **COMBINED HOUSING AND SECURING DEVICE**

[75] Inventor: **Stephen A. Nemeckay**, Detroit, Mich.

[73] Assignee: **Dexter Automatic Products Company**,
Dexter, Mich.

[**] Term: **14 Years**

[21] Appl. No.: **34,807**

[22] Filed: **Feb. 13, 1995**

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 312,816, Sep. 27, 1994, Pat. No. 5,538,299.

[51] **LOC (6) Cl.** **08-05**

[52] **U.S. Cl.** **D8/354**

[58] **Field of Search** D8/349, 354, 382,
D8/394-396; 403/384, 344; 248/56, 59,
62, 68.1, 74.1-74.4, 58; 292/305

[56] References Cited

U.S. PATENT DOCUMENTS

- D. 296,866 7/1988 Behring .
- 714,605 11/1902 Potter .
- 727,707 5/1903 Stauffer et al. .
- 772,634 10/1904 Snyder .
- 860,369 7/1907 Grundy .
- 918,078 4/1909 McCaffrey .
- 926,426 9/1909 Koch .
- 1,151,131 8/1915 Starliper .
- 1,661,868 3/1928 Armstrong et al. .
- 2,191,444 2/1940 Fleming .
- 2,671,355 3/1954 Hawkins .
- 2,732,920 1/1956 Newton .
- 2,806,722 9/1957 Atkins .
- 2,814,067 11/1957 Bowden .
- 2,953,874 9/1960 Kindorf 248/58 X
- 3,023,036 2/1962 Taylor .
- 3,033,599 5/1962 Hudson et al. .
- 3,162,084 12/1964 Wurzel .
- 3,324,613 6/1967 Duboff .
- 3,566,435 3/1971 Nakamura .
- 3,955,828 5/1976 Boudreau .

- 4,415,194 11/1983 Bauer .
- 4,557,470 12/1985 Link .
- 4,709,949 12/1987 Umezawa et al. .
- 4,723,765 2/1988 Pearson .
- 4,777,698 10/1988 Lord .
- 4,815,163 3/1989 Simmons .
- 4,824,082 4/1989 Schaupp .
- 4,865,169 9/1989 Rachels et al. .

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

- 1425116 9/1988 U.S.S.R. .
- 8218802 10/1959 United Kingdom .
- 2139282 11/1984 United Kingdom .

Primary Examiner—Holly Baynham
Attorney, Agent, or Firm—Weintraub, DuRoss & Brady

[57] CLAIM

The ornamental design for a combined housing and securing device, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a combined housing and securing device, showing a first embodiment of my new design;

FIG. 2 is a top plan view thereof;

FIG. 3 is a right side elevational view thereof;

FIG. 4 is a front elevational view thereof;

FIG. 5 is a left-side elevational view thereof;

FIG. 6 is a rear elevational view thereof;

FIG. 7 is a bottom plan view thereof;


FIG. 8 is a right-side view of a combined housing and securing device, showing a second embodiment of my new design with the opposite side being a mirror image thereof; and,

FIG. 9 is a bottom plan view thereof.

The undisclosed top view of the second embodiment is identical in appearance to the top view of the first embodiment.

The undisclosed front and rear views of the second embodiment are similar in appearance to the same views of the first embodiment except for the presence of continuous curved surface in the second embodiment.

1 Claim, 1 Drawing Sheet



U.S. PATENT DOCUMENTS

4,915,538	4/1990	Golden et al. .	5,090,089	2/1992	Schulte et al. .	
4,925,230	5/1990	Shelton .	5,104,161	4/1992	Kautt .	
5,000,640	3/1991	Haas .	5,331,718	7/1994	Gilbert et al. .	
5,024,303	6/1991	Kosloff .	5,335,396	8/1994	Dolan .	
			5,406,032	4/1995	Clayton et al.	248/56 X





FIG 3




FIG 4




FIG 5




FIG 6





FIG 7




FIG 8




FIG 9