



US00D389871S

United States Patent [19]
Young

[11] **Patent Number:** **Des. 389,871**
[45] **Date of Patent:** ****Jan. 27, 1998**

[54] **SAFETY SIGN**

D. 186,482 10/1959 Schwartz et al. D10/109 X
D. 255,107 5/1980 Slepetz D10/114
D. 360,846 8/1995 Kallionpaa D29/41 X

[75] **Inventor:** **Scot Young**, West Midlands, Great Britain

[73] **Assignee:** **Scot Young Research, Inc.**, St. Joseph, Mo.

[**] **Term:** **14 Years**

Primary Examiner—Susan J. Lucas
Assistant Examiner—Jennifer Register
Attorney, Agent, or Firm—Wm. Bruce Day

[21] **Appl. No.:** **57,677**

[22] **Filed:** **Jul. 30, 1996**

[51] **LOC (6) Cl.** **20-02**

[52] **U.S. Cl.** **D20/41; D10/109**

[58] **Field of Search** D10/10, 17, 41,
D10/113, 114, 109; 40/455, 584, 612, 557,
591; D25/126, 127; 246/479-485; 116/63 R,
63 P, 63 C

[57] **CLAIM**

The ornamental design for a safety sign, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of the safety sign according to the present invention;

FIG. 2 is a front elevational view of the safety sign of FIG. 1 the rear elevation being a mirror image;

FIG. 3 is a side elevation view of the safety sign of FIG. 1 the opposite side being a mirror image; and,


FIG. 4 is a top plan view of the safety sign of FIG. 1.

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 78,442 5/1929 Carson D20/41

1 Claim, 1 Drawing Sheet






Fig. 1.

Fig. 2.





Fig. 3.

Fig. 4.

