



US00D390608S

**United States Patent** [19]  
**Holden**

[11] **Patent Number: Des. 390,608**  
[45] **Date of Patent: \*\*Feb. 10, 1998**

[54] **FIRE SAFETY LABEL**

[76] Inventor: **George M. Holden**, 3 Superior Avenue-Unit #407, Etobicoke, Ontario, Canada, M8V 2M2

[\*\*] Term: **14 Years**

[21] Appl. No.: **70,475**

[22] Filed: **May 8, 1997**

[51] **LOC (6) Cl.** ..... **19-08**

[52] **U.S. Cl.** ..... **D20/27; D20/22**

[58] **Field of Search** ..... **D20/10, 22, 27, D20/40, 42, 11; 40/124.1, 630, 638; 283/81, 75, 109, 114, 500**

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

D. 242,502 11/1976 Hubitsky ..... D20/42 X

**OTHER PUBLICATIONS**

Three Dimensional Markers, TDM4, Seton Cataog, p. J67, Aug. 1987.

Vinyl Extinguisher Instruction Decals, Seton Catalog, p. J67, Aug. 1987.

*Primary Examiner*—Susan J. Lucas  
*Assistant Examiner*—Jennifer Register

[57] **CLAIM**

The ornamental design for a fire safety label, as shown and described.

**DESCRIPTION**

FIG. 1 is a front plan view of the fire safety label of the present invention;

FIG. 2 is a back plan view of the fire safety label of FIG. 1;

FIG. 3 is a left side plan view of the fire safety label of FIG. 1;


FIG. 4 is a right side plan view of the fire safety label of FIG. 1;


FIG. 5 is a top plan view of the fire safety label of FIG. 1; and,

FIG. 6 is a bottom plan view of the fire safety label of FIG. 1.


The claimed design is shaded to indicate a translucent surface.

**1 Claim, 3 Drawing Sheets**





*Fig. 1*



*Fig. 2*



*Fig. 3*



*Fig. 4*



*Fig. 5*



*Fig. 6*