



US00D391015S

# United States Patent [19] Montoya

[11] Patent Number: Des. 391,015

[45] Date of Patent: \*\*Feb. 17, 1998

[54] **CYLINDRICAL SMOKING STORAGE  
DEVICE**

[75] Inventor: **Mark T. Montoya**, W. Lafayette, Ind.

[73] Assignee: **Katoya Products, Inc.**, West Lafayette, Ind.

[\*\*] Term: **14 Years**

[21] Appl. No.: **66,416**

[22] Filed: **Feb. 13, 1997**

[51] LOC (6) Cl. .... **27-06**

[52] U.S. Cl. .... **D27/187; D27/189**

[58] Field of Search ..... **206/270, 255,  
206/236, 237, 238, 239, 240, 241, 261,  
269, 249, 250, 256; D9/529; 30/113; D28/88;  
D27/172, 183, 186, 187, 188, 189, 190,  
191, 194**

[56] **References Cited**

**U.S. PATENT DOCUMENTS**

D. 254,242	2/1980	Morin	.....	D7/615
498,695	5/1893	Powell	.	
1,089,457	3/1914	Berriman	.....	206/255 X
2,346,087	4/1944	Sevastopulos	.....	206/255
2,543,190	6/1951	Musekamp	.....	206/255 X
3,861,523	1/1975	Fountain et al.	.....	206/267 X
4,214,658	7/1980	Crow	.	
5,465,738	11/1995	Rowland	.....	206/242 X

*Primary Examiner*—Susan J. Lucas  
*Assistant Examiner*—Jennifer Register  
*Attorney, Agent, or Firm*—Woodard, Emhardt, Naughton  
Moriarty & McNett


[57] **CLAIM**

The ornamental design for a cylindrical smoking storage device, as shown and described.

**DESCRIPTION**

FIG. 1 is a front view of the preferred embodiment with the rear view, left side view, and right side view being mirror images thereof;  
FIG. 2 is a bottom view;  
FIG. 3 is a top view of the device in a closed state;  
FIG. 4 is a top view in a first open state;  
FIG. 5 is a top view in a second open state;  
FIG. 6 is a front view of the device of FIG. 5 with the rear view being a mirror image thereof;  
FIG. 7 is a left side view of the device of FIG. 5 with the right side view being a mirror image thereof;  
FIG. 8 is a front view of a first alternate embodiment;  
FIG. 9 is a rear view of the device of FIG. 8;  
FIG. 10 is a left side view of the device of FIG. 8 with the right side view being a mirror image thereof;  
FIG. 11 is a bottom view of the device of FIG. 8;  
FIG. 12 is a top view of the device of FIG. 8 in a closed state;  
FIG. 13 is a top view of the device of FIG. 8 in a first open state;  
FIG. 14 is a top view of the device of FIG. 8 in a second open state;  
FIG. 15 is a front view of the device of FIG. 14 with the rear view being a mirror image thereof;  
FIG. 16 is a left side view of the device of FIG. 14; and,  
FIG. 17 is a right side view of the device of FIG. 14.

**1 Claim, 3 Drawing Sheets**






Fig. 3




Fig. 1




Fig. 2




Fig. 5




Fig. 6




Fig. 4







Fig. 7




**Fig. 12**




**Fig. 8**




**Fig. 10**




**Fig. 9**




**Fig. 11**




**Fig. 14**




**Fig. 13**



**Fig. 16**



**Fig. 15**



**Fig. 17**