



US00D392407S

United States Patent [19]
Johnson et al.

[11] **Patent Number:** **Des. 392,407**
[45] **Date of Patent:** ****Mar. 17, 1998**

[54] **LIGHT FIXTURE**

[75] **Inventors:** **Richard A. Johnson**, Milwaukee;
Rupert O. Yantz, West Bend; **Mark T. Dane**, Milwaukee; **Richard C. Mayer**, Brookfield, all of Wis.
[73] **Assignee:** **Phoenix Products Company, Inc.**, Milwaukee, Wis.
[**] **Term:** **14 Years**

[21] **Appl. No.:** **43,390**
[22] **Filed:** **Aug. 30, 1995**
[51] **LOC (6) Cl.** **26-05**
[52] **U.S. Cl.** **D26/67; D26/24; D26/104**
[58] **Field of Search** **D26/67, 68, 61, D26/93, 104, 110, 24; 362/153, 153.1, 35, 267, 431, 410-413**

[56] **References Cited**

U.S. PATENT DOCUMENTS

D. 157,613	3/1950	McCurry		D26/68 X
D. 231,013	3/1974	Bonati et al.		D26/104
D. 333,529	2/1993	Denison et al.		D26/68
D. 358,902	5/1995	Webster, III		D26/67 X
1,069,150	8/1913	Larson		362/35 X
2,947,970	8/1960	Van Oosten		362/35
4,188,655	2/1980	Tallon et al.		362/80
4,306,279	12/1981	Cohen		362/365
4,355,349	10/1982	Simons et al.		362/153
4,523,263	6/1985	Poyer		362/431 X
4,533,984	8/1985	Gatton		362/232
4,692,848	9/1987	Poyer		362/431 X
4,757,428	7/1988	Ryder et al.		362/66
4,761,717	8/1988	McMahan et al.		362/66
4,893,224	1/1990	Tinley		362/287
4,999,757	3/1991	Poppenheimer		362/287
5,032,964	7/1991	Endo et al.		362/61
5,230,559	7/1993	Porter et al.		362/153.1

FOREIGN PATENT DOCUMENTS

4-73802	3/1992	Japan		362/35
---------	--------	-------	-------	--------

OTHER PUBLICATIONS

Capritrack Catalog. ©1986, p. 4, Spotlight #KR711.

Primary Examiner—Susan J. Lucas
Attorney, Agent, or Firm—Quarles & Brady

[57] **CLAIM**

The ornamental design for a light fixture, as shown and described.

DESCRIPTION

FIG. 1 is a top perspective view of a light fixture showing our new design;
FIG. 2 is a front elevational view thereof, the rear elevational view thereof being a mirror image of FIG. 2;
FIG. 3 is a top elevational view thereof;
FIG. 4 is a right side elevational view thereof, the left side elevational view being a mirror image of FIG. 4;
FIG. 5 is a bottom elevational view thereof;
FIG. 6 is a right side elevational view of a second embodiment showing our new design which is identical to the embodiment of FIGS. 1-5 but with the addition of two continuous circumferential grooves as shown, the left side elevational view being a mirror image of FIG. 6;
FIG. 7 is a front elevational view of the embodiment of FIG. 6, the rear elevational view thereof being a mirror image of FIG. 7 and the top and bottom elevational views thereof being identical to FIGS. 3 and 5, respectively;
FIG. 8 is a right side elevational view of a third embodiment showing our new design, which is identical to the embodiment of FIGS. 1-5, but with a flat lens rather than a convex lens, the left side elevational view being a mirror image of FIG. 8; and,
FIG. 9 is a front elevational view of the embodiment of FIG. 8, the rear elevational view thereof being a mirror image of FIG. 9 and the top and bottom elevational views thereof being identical to FIGS. 3 and 5, respectively.
The broken line representations of fittings in FIGS. 1, 2 and 4-9 are shown for environment only and form no part of the present invention.

1 Claim, 4 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

