



US00D394219S

United States Patent [19]

Morrow et al.

[11] Patent Number: Des. 394,219

[45] Date of Patent: **May 12, 1998

[54] THERMOSTAT

[75] Inventors: James Morrow, Oak Park; Brian Day, Des Plaines, both of Ill.; David Stearns, Wichita, Kans.; Gary Van Deursen, Evergreen, Colo.

[73] Assignee: Coleman Safety and Security Products, Inc., Downers Grove, Ill.

[**] Term: 14 Years

[21] Appl. No.: 74,945

[22] Filed: Aug. 13, 1997

[51] LOC (6) Cl. 10-04

[52] U.S. Cl. D10/50

[58] Field of Search D10/49, 50; 165/11.1, 165/13, 22, 32-41; 236/1 B, 46 R, 47, 49.3, 87, 94; 337/360, 380; 364/557

[56] References Cited

U.S. PATENT DOCUMENTS

- D. 238,583 1/1976 Russell D10/49
- D. 377,909 2/1997 Smith D10/50

Primary Examiner—Antoine Duval Davis
Attorney, Agent, or Firm—James H. Phillips; Michael A. Lechter

[57] CLAIM


The ornamental design for a thermostat, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a first embodiment of our design with a variable configuration section shown in dashed lines;

FIG. 2 is a front view of the first embodiment of our design with a variable configuration section shown in dashed lines; FIG. 3 is a rear view of the first embodiment of our design; FIG. 4 is a left side view of the first embodiment of our design; FIG. 5 is a top view of the first embodiment of our design; FIG. 6 is a bottom view of the first embodiment of our design; FIG. 7 is a partial front view showing a second embodiment of the variable configuration section; FIG. 8 is a partial front view showing a third embodiment of the variable configuration section and with optional adjacent switches; FIG. 9 is a partial right side view showing the disposition of the optional adjacent switches; FIG. 10 is a partial left side view showing the disposition of the optional adjacent switches; FIG. 11 is a partial front view showing a fourth embodiment of the variable configuration section and with the optional adjacent switches; FIG. 12 is a partial front view showing a fifth embodiment of the variable configuration section; FIG. 13 is a perspective view of a sixth embodiment of design with a variable configuration section shown in dashed lines; FIG. 14 is a front view of the sixth embodiment of our design with a variable configuration section shown in dashed lines; FIG. 15 is a rear view of the sixth embodiment of our design; FIG. 16 is a left side view of the sixth embodiment of our design; FIG. 17 is a top view of the sixth embodiment of our design; and, FIG. 18 is a bottom view of the sixth embodiment of our design. The broken line showing is for illustrative purposes only and forms no part of the claimed design.

1 Claim, 3 Drawing Sheets






FIG. 1




FIG. 2




FIG. 4




FIG. 3




FIG. 6




FIG. 5




FIG. 7




FIG. 9




FIG. 8



FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14



FIG. 16




FIG. 15




FIG. 17




FIG. 18